

Specification Sheet

Part Number: ATS10266210

The ATS3080 cable tie is designed for optimized material utilization by using an innovative two-piece system consisting of individual strap and closures.

Waste-free cable tie system eliminates down time due to cleaning and opening waster containers.

Bundle diameter is mechanically detected and allows a flush cut off of the strap.

Available in reels of 1,640 feet of strap and 5,000 closures.



Cable Ties for ATS3080, 50lb Tensile Strength, PA66HSUV, Black, 5000/reel

Article Number 102-66210

Type Closures_Black_ATS

Color Black (BK)

Quantity Per pcs.

Product Description HellermannTyton offers the widest range of automatic cable tie tool systems which cover cable tie tensile strengths of 18, 30, and 50 pounds with bundle diameters between 1/16" to over 3". For use with HellermannTyton's Automatic Tool Systems.

Short Description Cable Ties for ATS3080, 50lb Tensile Strength, PA66HSUV, Black, 5000/reel

Global Part Name Closures_Black_ATS-PA66HSUV-BK

Minimum Tensile Strength (Imperial)	50.0
Minimum Tensile Strength (Metric)	225
Length L (Imperial)	0.35
Length L (Metric)	9.0
Identification Plate Position	none
Reel Diameter (Imperial)	15.25
Reel Diameter (Metric)	387
Reel Width (Imperial)	3.5
Reel Width (Metric)	88.9
Releasable Closure	No
Variant	closures on reel
Width W (Imperial)	0.31
Width W (Metric)	8.0
Bundle Diameter Min (Metric)	0.0
Bundle Diameter Max (Imperial)	3.14
Bundle Diameter Max (Metric)	100

Height H (Imperial)	0.212
Height H (Metric)	5.4
Material	Polyamide 6.6 heat and UV stabilized (PA66HSUV)
Material Shortcut	PA66HSUV
Flammability	UL 94 V-2
UV Resistant (Yes/No)	Yes
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	5000
Package Quantity (Metric)	5000
Customs Number	3926909988
Reel Weight (Imperial)	3.5
Reel Weight (Metric)	1.58

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)