

Specification Sheet

Part Number: AT2060

Fast: Cable ties are installed quickly with one easy trigger depression, increasing productivity while decreasing labor costs.

Reliable: HellermannTyton's automatic cable tie systems have been tested to perform extremely consistently, without interruption to workflow.

Ergonomic: The ergonomic design of the automatic cable tie tool systems feature a comfortable grip, low weight, and easy trigger depression to reduce installer effort and strain while installing cable ties.

Providing Valuable Operator Feedback: Equipped with a self diagnostic LCD information screen, the automatic cable tie system easily guides the user through the cycles of cable tie installations.

Flexible Manufacturing Versatility: HellermannTyton's cable tie tool systems support principles of flexible manufacturing requirements and environments.

Uniform Fastening Quality: HellermannTyton's automatic cable tie systems feature adjustable tension control to deliver consistent levels of cable tie fastening.

Range: HellermannTyton offers the widest range of automatic cable tie tool systems which cover cable tie tensile strengths of 18, 30 and 50 pounds with bundle diameters between 1/16" to over 3".



AT2060 Auto Tool, Installs 30lb cable ties up to 1 1/4", Includes power supply and cords, 1/pkg

Article Number 103-00000

Type AT2060

Color Black (BK)

Quantity Per	case
Product Description	<p>HellermannTyton's AT2060 system includes tool, power supply, power cord, tool cord, and maintenance and operation manual. This system can be used in handheld, bench mount, and overhead assembly configurations. The versatile overhead assembly option provides the ultimate integration into the customer's manufacturing area.</p> <p>HellermannTyton's autotool AT2060 is powered by a standard 110 AC 27V electrical outlet that the power supply converts to a low DC voltage for the tool.</p>
Short Description	AT2060 Auto Tool, Installs 30lb cable ties up to 1 1/4", Includes power supply and cords, 1/pkg
Global Part Name	AT2060-MET/PL-BK
Length L (Imperial)	14.20
Length L (Metric)	361.2
Voltage Range	27 Volt
Width W (Imperial)	2.6
Width W (Metric)	66.4
Bundle Diameter Min (Imperial)	0.06
Bundle Diameter Min (Metric)	1.50
Bundle Diameter Max (Imperial)	1.25
Bundle Diameter Max (Metric)	31.75

Cable Ties	T30RA30, T30RA3000
Cycle Time	1.2
Power supply unit	85-265 VAC
Height H (Imperial)	10.62
Height H (Metric)	269.7
Tension Setting Tools	Adjustable
Cable Tie Width Max (Imperial)	0.14
Cable Tie Width Max (Metric)	3.6
Power Supply	Electrical with Power Pack
Material	Metal (MET) Plastic (PL)
Material Shortcut	PL MET
UV Resistant (Yes/No)	No
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	1

Package Quantity (Metric) 1

Customs Number 8467290095

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)