

Specification Sheet

Part Number: T30RA3000



Cable Ties for AT2060, 30lb Tensile Strength, PA66, Natural, 3000/reel

Article Number 103-00001

Type T30RA

Color Natural (NA)

Features & Benefits

- The AT2060 cable tie system is designed for automatic installation on bundles up to 1.25" and a minimum tensile strength of 30 lbs.
- Available in reels of 3,000 each or bandoliers of 30 each.

Quantity Per reel

Product Description Cable ties for use with HellermannTyton's AT2060 automatic cable tie tool

Short Description Cable Ties for AT2060, 30lb Tensile Strength, PA66, Natural, 3000/reel

Global Part Name T30RA-PA66-NA

Minimum Tensile Strength (Imperial) 30.0

Minimum Tensile Strength (Metric) 135.0

Length L (Imperial) 6.0

Length L (Metric) 152.4

Identification Plate Position none

Reel Diameter (Imperial) 17.7

Reel Diameter (Metric) 450.0

Reel Width (Imperial) 7.197

Reel Width (Metric) 182.8

Voltage Range 27 Volt

Releasable Closure No

Width W (Imperial) 0.14

Width W (Metric) 3.6

Bundle Diameter Min (Imperial) 0.06

Bundle Diameter Min (Metric) 1.5

Bundle Diameter Max (Imperial)	1.25
Bundle Diameter Max (Metric)	31.75
Thickness T (Imperial)	0.05
Thickness T (Metric)	1.2
Cycle Time	1.2 seconds
Power Supply	Electrical
Tension Force	Adjustable
Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
US MIL SPEC	MS3367-5-9, Class 2
Flammability	UL 94 V2
Halogen free	Yes
Operating Temperature (Metric)	-40°F to +185°F (-40°C to +85°C)
ROHS Complaint	Yes
Certification/Specification WEB	CAGE Code 53421 UL-ZODZ2.E64139

UL Recognized (US)	Yes
UL Recognized (US and Canada)	Yes
Package Quantity(Imperial)	3000
Package Quantity (Metric)	3000
Customs Number	3926909988
Weight (Metric)	1.8
Weight (Imperial)	3.9
Reel Weight (Imperial)	7
Reel Weight (Metric)	3.175