

## Specification Sheet

Part Number: T30RA30



The AT2060 cable tie system is designed for automatic installation on bundles up to 1.25" and a minimum tensile strength of 30 lbs.

Available in reels of 3,000 each or bandoliers of 30 each.

Cable Ties for AT2060, 30lb Tensile Strength, PA66, Natural, 30/bandolier, 600/pkg

<b>Article Number</b>	103-00002
<b>Type</b>	T30RA
<b>Color</b>	Natural (NA)
<b>Quantity Per</b>	bag
<b>Product Description</b>	Cable ties for use with HellermannTyton's AT2060 automatic cable tie tool
<b>Short Description</b>	Cable Ties for AT2060, 30lb Tensile Strength, PA66, Natural, 30/bandolier, 600/pkg
<b>Global Part Name</b>	T30RA-PA66-NA

<b>Minimum Tensile Strength (Imperial)</b>	30.0
<b>Minimum Tensile Strength (Metric)</b>	135.0
<b>Length L (Imperial)</b>	6.0
<b>Length L (Metric)</b>	152.4
<b>Identification Plate Position</b>	none
<b>Reel Diameter (Imperial)</b>	17.7
<b>Reel Diameter (Metric)</b>	450.0
<b>Reel Width (Imperial)</b>	7.197
<b>Reel Width (Metric)</b>	182.8
<b>Voltage Range</b>	27 Volt
<b>Releasable Closure</b>	No
<b>Width W (Imperial)</b>	0.14
<b>Width W (Metric)</b>	3.6
<b>Bundle Diameter Min (Imperial)</b>	0.06
<b>Bundle Diameter Min (Metric)</b>	1.5
<b>Bundle Diameter Max (Imperial)</b>	1.25
<b>Bundle Diameter Max (Metric)</b>	31.75

<b>Cycle Time</b>	1.2 seconds
<b>Tension Setting Tools</b>	Adjustable
<b>Power Supply</b>	Electrical
<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>US MIL SPEC</b>	MS3367-5-9, Class 2
<b>Flammability</b>	UL 94 V2
<b>Operating Temperature</b>	-40°F to +185°F (-40°C to +85°C)
<b>Certification/Specification</b>	CAGE Code 53421 UL-ZODZ2.E64139
<b>UL Recognized (US)</b>	Yes
<b>UL Recognized (US and Canada)</b>	Yes
<b>Package Quantity (Imperial)</b>	600
<b>Package Quantity (Metric)</b>	600
<b>Customs Number</b>	3926909988

**Reel Weight (Imperial)** 7

**Reel Weight (Metric)** 3.175