

Specification Sheet

Part Number: T30RA30000HS



Cable Ties for AT2060, 30lb Tensile Strength, PA66HS, Black, 3000/reel

Article Number	103-00004
Type	T30RA
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none">• The AT2060 cable tie system is designed for automatic installation on bundles up to 1.25" and a minimum tensile strength of 30 lbs.• Available in reels of 3,000 each or bandoliers of 30 each.
Quantity Per	reel
Product Description	Includes AT2060 tool, power supply, power cord, tool cord, and maintenance and operation manual.
Short Description	Cable Ties for AT2060, 30lb Tensile Strength, PA66HS, Black, 3000/reel
Global Part Name	T30RA-PA66HS-BK

Minimum Tensile Strength (Imperial)	30.0
Minimum Tensile Strength (Metric)	135.0
Length L (Imperial)	6.0
Length L (Metric)	152.4
Identification Plate Position	none
Reel Diameter (Imperial)	17.7
Reel Diameter (Metric)	450.0
Reel Width (Imperial)	7.197
Reel Width (Metric)	182.8
Voltage Range	27 Volt
Releasable Closure	No
Width W (Imperial)	0.14
Width W (Metric)	3.6
Bundle Diameter Min (Imperial)	0.06
Bundle Diameter Min (Metric)	1.5
Bundle Diameter Max (Imperial)	1.25
Bundle Diameter Max (Metric)	31.75

Thickness T (Imperial) 0.05

Thickness T (Metric) 1.2

Cycle Time 1.2 seconds

Power Supply Electrical

Tension Force Adjustable

Material Polyamide 6.6 heat stabilized (PA66HS)

Material Shortcut PA66HS

Flammability UL 94 V2

Halogen free Yes

Operating Temperature (Metric) -40°F to +275°F (-40°C to +135°C)

ROHS Complaint Yes

UL Recognized (US) Yes

UL Recognized (US and Canada) Yes

Package Quantity(Imperial) 3000

Package Quantity (Metric) 3000

Customs Number	3926909987
Weight (Metric)	1.8
Weight (Imperial)	3.9
Reel Weight (Imperial)	7
Reel Weight (Metric)	3.175