

Specification Sheet

Part Number: 103-00042



The AT2060 cable tie system is designed for automatic installation on bundles up to 1.25" and a minimum tensile strength of 30 lbs.

Available in reels of 3,000 each or bandoliers of 30 each.

Complies with MS3367-5-9, Class 2 and SAE-AS33671.

MilSpec Cable Tie for AT2060, MS3367, 30lb Tensile Strength, PA66, Natural, 3000/reel

Article Number 103-00042

Type T30RA3000

Color Natural (NA)

Quantity Per box

Product Description Includes AT2060 tool, power supply, power cord, tool cord, and maintenance and operation manual. Specially manufactured to comply with Military Specification MS3367-5-9, Class 2 and SAE-AS33671.

Short Description MilSpec Cable Tie for AT2060, MS3367, 30lb Tensile Strength, PA66, Natural, 3000/reel

Global Part Name T30RA3000-PA66-NA

Minimum Tensile Strength (Imperial)	30
Minimum Tensile Strength (Metric)	133.44
Length L (Imperial)	6.0
Length L (Metric)	152.4
Identification Plate Position	none
Reel Diameter (Imperial)	17.7
Reel Diameter (Metric)	450
Reel Width (Imperial)	7.197
Reel Width (Metric)	182.8
Voltage Range	27 Volt
Releasable Closure	No
Width W (Imperial)	0.14
Width W (Metric)	3.6
Bundle Diameter Max (Imperial)	1.25
Bundle Diameter Max (Metric)	31.0
Cycle Time	1.2 seconds

Tension Setting Tools	Adjustable
Power Supply	Electrical
Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
US MIL SPEC	MS3367-5-9, Class 2 SAE-AS33671
Flammability	UL 94 V-2
Operating Temperature	-40°F to +185°F (-40°C to +85°C)
Package Quantity (Imperial)	600
Package Quantity (Metric)	2
Reel Weight (Imperial)	7
Reel Weight (Metric)	3.175