


## Specification Sheet

Part Number: 109-00014



Open-head design with easily detectable slot opening allows for swift and easy insertion

Pre-lock feature allows for a temporary hold

The large ribbed tail permits an ergonomic installation

Two rails on the strap ensure guidance through the cable tie head

Q Tie, 9.8" Long, 30lb Tensile Strength, PA66, Natural, 100/pkg

Article Number 109-00014

Type Q30LR

Color Natural (NA)

Quantity Per bag

**Product Description** Q-Ties have a distinctive open-style head, a pre-lock function, and a large ribbed tail. The easily detectable slot opening offered with the tail and tie head provides ease of placement when working with gloves or for blind applications with limited view of the installation. The pre-lock feature allows for temporary holding of cable and wire bundles, permitting additional cables and wires to be placed without destroying the cable tie. Q-Ties can be tensioned by hand or with one of HellermannTyton's mechanical cable tie application tools.

**Short Description** Q Tie, 9.8" Long, 30lb Tensile Strength, PA66, Natural, 100/pkg

Global Part Name Q30LR-PA66-NA

Minimum Tensile Strength (Imperial) 30.0

Minimum Tensile Strength (Metric) 130

Length L (Imperial) 9.8

Length L (Metric) 250

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.14

Width W (Metric) 3.6

Bundle Diameter Min (Imperial) 0.06

Bundle Diameter Min (Metric) 3.0

Bundle Diameter Max (Imperial) 2.6

Bundle Diameter Max (Metric) 65.0

Thickness T (Imperial) 0.05

Thickness T (Metric)	1.3
Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Flammability	UL 94 V-2
Halogen Free	Yes
Operating Temperature	-40°F to +185°F (-40°C to +85°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	100
Package Quantity (Metric)	100
Customs Number	3926909988