

Specification Sheet

Part Number: 109-00022



Q Tie, 16.1" Long, 50lb Tensile Strength, PA66, Natural, 100/pkg

Article Number

109-00022

Type

Q50L

Color

Natural (NA)

Features & Benefits

- Open-head design with easily detectable slot opening allows for swift and easy insertion
- Pre-lock feature allows for a temporary hold
- The large ribbed tail permits an ergonomic installation
- Two rails on the strap ensure guidance through the cable tie head

Quantity Per

bag

Product Description

Q-Ties have a distinctive open-style head, a pre-lock function, and a large ribbed tail. The easily detectable slot opening offered with the tail and tie head provides ease of placement when working with gloves or for blind applications with limited view of the installation. The pre-lock feature allows for temporary holding of cable and wire bundles, permitting additional cables and wires to be placed without destroying the cable tie. Q-Ties can be tensioned by hand or with one of HellermannTyton's mechanical cable tie application tools.

| | |
|--------------------------------------------|------------------------------------------------------------------|
| Short Description | Q Tie, 16.1" Long, 50lb Tensile Strength, PA66, Natural, 100/pkg |
| Global Part Name | Q50L-PA66-NA |
| Minimum Tensile Strength (Imperial) | 50.0 |
| Minimum Tensile Strength (Metric) | 220 |
| Length L (Imperial) | 16.1 |
| Length L (Metric) | 410 |
| Identification Plate Position | none |
| Releasable Closure | No |
| Tie Closure | plastic pawl |
| Variant | Inside Serrated |
| Width W (Imperial) | 0.19 |
| Width W (Metric) | 4.7 |
| Bundle Diameter Min (Imperial) | 0.12 |
| Bundle Diameter Max (Imperial) | 4.3 |
| Bundle Diameter Max (Metric) | 110.0 |
| Thickness T (Imperial) | 0.06 |
| Thickness T (Metric) | 1.5 |

| | |
|----------------------------------------|--------------------------------------------------------|
| Material | Polyamide 6.6 (PA66) |
| Material Shortcut | PA66 |
| Flammability | UL 94 V2 |
| Halogen free | Yes |
| Operating Temperature (Metric) | -40°F to +185°F (-40°C to +85°C) |
| Reach Complaint(Article 33) | Yes |
| ROHS Complaint | Yes |
| Certification/Specification WEB | UL ANSI/UL 1565 UL ANSI/UL 62275 UL ANSI/UL 746B |
| UL Listed (US and Canada) | Yes |
| UL Listed (US | Yes |
| Package Quantity(Imperial) | 100 |
| Package Quantity (Metric) | 100 |
| Customs Number | 3926909987 |
| Content Unit(BMEcat) | pcs. |

© 2019 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)