

Specification Sheet

Part Number: T50I2M4UL



Cable Tie, 12" Long, UL Rated, 50lb Tensile Strength, PA66, Red, 1000/pkg

| | |
|---------------------|---|
| Article Number | 111-00519 |
| Type | T50I |
| Color | Red (RD) |
| Features & Benefits | <ul style="list-style-type: none">•Engineered and manufactured for maximum performance and quality.•Made from 100% high-quality plastic to ensure efficient recycling.•Inside serration for a strong grip onto bundles.•Easy application either manually or with a tensioning tool.•Bent tail allows for simpler insertion. |
| Quantity Per | bag |

Product Description

T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

| | |
|--|---|
| Short Description | Cable Tie, 12" Long, UL Rated, 50lb Tensile Strength, PA66, Red, 1000/pkg |
| Global Part Name | T50I-PA66-RD |
| Minimum Tensile Strength (Imperial) | 50.0 |
| Minimum Tensile Strength (Metric) | 225.0 |
| Length L (Imperial) | 12.0 |
| Length L (Metric) | 305.0 |
| Identification Plate Position | none |
| Releasable Closure | No |
| Tie Closure | plastic pawl |
| Variant | Inside Serrated |
| Width W (Imperial) | 0.18 |
| Width W (Metric) | 4.6 |
| Bundle Diameter Min (Imperial) | 0.06 |
| Bundle Diameter Min (Metric) | 1.5 |
| Bundle Diameter Max (Imperial) | 3.2 |
| Bundle Diameter Max (Metric) | 81.3 |
| Thickness T (Metric) | 1.2 |

| | |
|-----------------|----------------------|
| Material | Polyamide 6.6 (PA66) |
|-----------------|----------------------|

| | |
|--------------------------|------|
| Material Shortcut | PA66 |
|--------------------------|------|

| | |
|--------------------|------------|
| US MIL SPEC | MS3367-7-2 |
|--------------------|------------|

SAE-AS33671

Flammability

UL 94 V2

Halogen free

Yes

Operating Temperature (Metric)

-40°F to +185°F (-40°C to +85°C)

ROHS Complaint

Yes

Certification/Specification WEB

UL-ZODZ.E64139 CAGE Code 53421

UL Recognized (US)

Yes

UL Listed (US and Canada)

Yes

UL Recognized (US and Canada)

Yes

UL Listed (US)

Yes

| | |
|-----------------------------------|------|
| Package Quantity(Imperial) | 1000 |
|-----------------------------------|------|

| | |
|----------------------------------|------|
| Package Quantity (Metric) | 1000 |
|----------------------------------|------|

Customs Number

3926909988

© 2019 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)