

Specification Sheet

Part Number: 111-01266



Solar Tie, 11.9" Long, 56lb Tensile Strength, PA11W, Black, 100/pkg

Article Number 111-01266

Type GL300

Color Black (BK)

Features & Benefits

- Nylon 11 cable ties provide excellent resistance to UV, chemical and moisture sensitive environments.
- Inside serrations and smooth edges allow for a strong grip on cables and wire bundles without damaging them.
- Head design provides high tensile strength with very low insertion force.

Quantity Per bag

Product Description	These inside serrated cable ties are manufactured from Polyamide 11 that provides excellent UV, chemical, and moisture resistance to allow for a longer life span in outdoor use. This material is recommended for applications exposed to metal oxides. The head design guarantees high tensile strength, as well as a low insertion force. Tensioning tools are available to ensure consistent and safe installation.
Short Description	Solar Tie, 11.9" Long, 56lb Tensile Strength, PA11W, Black, 100/pkg
Global Part Name	GL300-PA11W-BK
Minimum Tensile Strength (Imperial)	56
Minimum Tensile Strength (Metric)	250
Length L (Imperial)	11.9
Length L (Metric)	302.26
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.19
Width W (Metric)	4.8
Bundle Diameter Min (Imperial)	0.28

Bundle Diameter Min (Metric)	7.0
Bundle Diameter Max (Imperial)	3.2
Bundle Diameter Max (Metric)	80.0
Thickness T (Metric)	1.5
Material	Polyamide 11, UV-resistant (PA11W)
Material Shortcut	PA11W
Flammability	UL 94 HB
Operating Temperature (Metric)	-40°F to +221°F (-40°C to +105°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Certification/Specification WEB	DNV GL IEC 62275:2006
Use Conditions	For Indoor and Outdoor Use
Package Quantity(Imperial)	100
Package Quantity (Metric)	100

Customs Number 3926909988

Content Unit(BMEcat) pcs.