

Specification Sheet

Part Number: 111-01513

316 grade stainless steel offers excellent resistance to salt spray, corrosion, weather and chemical resistance

Polyester coating ensures smooth cable tie edges for minimal wear to bundles or hands

Coating prevents contact corrosion



High tensile strength for maximum performance and safety on heavy duty applications

Polyester Coated Stainless Steel Tie, 17" Long, 562lb Tensile Strength, SS316, Metal, 50/pkg

Article Number	111-01513
Type	MBT17UHFC
Color	Black (BK)
Quantity Per	bag

Product Description

HellermannTyton's MBT ties are fabricated from corrosion-resistant 316 stainless steel have a protective polyester coating. Stainless tie design includes a non-releasable locking feature for secure applications. Polyester coating provides smooth edges to make it safer for installers' hands and eliminates contact corrosion between dissimilar materials during application.

Short Description	Polyester Coated Stainless Steel Tie, 17" Long, 562lb Tensile Strength, SS316, Metal, 50/pkg
Global Part Name	MBT17UHFC-SP/SS316-BK
Minimum Tensile Strength (Imperial)	562
Minimum Tensile Strength (Metric)	2500
Length L (Imperial)	17.1
Length L (Metric)	434
Identification Plate Position	none
Releasable Closure	No
Tie Closure	ball bearing lock
Variant	Not Serrated
Width W (Imperial)	0.64
Width W (Metric)	16
Bundle Diameter Min (Imperial)	1.0
Bundle Diameter Min (Metric)	25
Bundle Diameter Max (Imperial)	4.9

Bundle Diameter Max (Metric)	125
Thickness T (Metric)	0.38
Material	Stainless Steel (SS316) Polyester (SP)
Material Shortcut	SP SS316
Flammability	Non-burning (except coating)
Halogen Free	Yes
Operating Temperature	-112°F to +1000°F (-80°C to +538°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	50
Package Quantity (Metric)	50
Customs Number	7326908695

