

Specification Sheet

Part Number: 111-01513



Polyester Coated Stainless Steel Tie, 17" Long, 562lb Tensile Strength, SS316, Metal, 50/pkg

Article Number 111-01513

Type MBT17UHFC

Color Black (BK)

Features & Benefits

- 316 grade stainless steel offers excellent resistance to salt spray, corrosion, weather and chemical resistance.
- Polyester coating ensures smooth cable tie edges for minimal wear to bundles or hands.
- Coating prevents contact corrosion.
- High tensile strength for maximum performance and safety on heavy duty applications.

Quantity Per bag

Product Description	HellermannTyton's MBT ties are fabricated from corrosion-resistant 316 stainless steel have a protective polyester coating. Stainless tie design includes a non-releasable locking feature for secure applications. Polyester coating provides smooth edges to make it safer for installers' hands and eliminates contact corrosion between dissimilar materials during application.
Short Description	Polyester Coated Stainless Steel Tie, 17" Long, 562lb Tensile Strength, SS316, Metal, 50/pkg
Global Part Name	MBT17UHFC-SP/SS316-BK
Minimum Tensile Strength (Imperial)	562
Minimum Tensile Strength (Metric)	2500
Length L (Imperial)	17.1
Length L (Metric)	434
Identification Plate Position	none
Releasable Closure	No
Tie Closure	ball bearing lock
Variant	No Serration
Width W (Imperial)	0.64
Width W (Metric)	16
Bundle Diameter Min (Imperial)	1.0

Bundle Diameter Min (Metric)	25
Bundle Diameter Max (Imperial)	4.9
Bundle Diameter Max (Metric)	125
Thickness T (Metric)	0.38
Material	Polyester (SP) Stainless Steel (SS316)
Material Shortcut	SS316 SP
Flammability	Non-Burning (except coating)
Halogen Free	Yes
Operating Temperature	-112°F to +1000°F (-80°C to +538°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	50
Package Quantity (Metric)	50
Customs Number	7326908695

Weight (Metric) 22.7

Weight (Imperial) 0.050