

## Specification Sheet

Part Number: 111-01572



Inside serrations allow for strong grip on cables and wire bundles  
Head design provides high tensile strength with very low insertion force

Heavy Duty Cable Tie, 21" Long, UL Rated, 175lb Tensile Strength, POMUV, Black, 25/pkg

Article Number 111-01572

Type T150M

Color Black (BK)

Quantity Per bag

Product Description HellermannTyton heavy duty T-Series cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

Short Description Heavy Duty Cable Tie, 21" Long, UL Rated, 175lb Tensile Strength, POMUV, Black, 25/pkg

Global Part Name T150M-POMUV-BK

Minimum Tensile Strength (Imperial) 175.0

Minimum Tensile Strength (Metric) 780.0

Length L (Imperial) 21.0

Length L (Metric) 530.0

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.35

Width W (Metric) 8.9

Bundle Diameter Min (Imperial) 0.31

Bundle Diameter Min (Metric) 8.0

Bundle Diameter Max (Imperial) 5.9

Bundle Diameter Max (Metric) 150.0

Thickness T (Metric) 1.9

Material	Polyacetal, UV stabilized (POMUV)
Material Shortcut	POMUV
Flammability	UL 94 HB
Halogen Free	Yes
Operating Temperature	-40°F to +194°F (-40°C to +90°C)
ROHS Compliant	Yes
Certification/Specification	UL 62275
UL Recognized (US)	Yes
UL Recognized (US and Canada)	Yes
Package Quantity (Imperial)	25
Package Quantity (Metric)	25
Customs Number	3926909988

