

## Specification Sheet

Part Number: 111-01572



Heavy Duty Cable Tie, 21" Long, UL Rated, 175lb Tensile Strength, POM, Black, 25/pkg

<b>Article Number</b>	111-01572
<b>Type</b>	T150M
<b>Color</b>	Black (BK)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>• Inside serrations allow for strong grip on cables and wire bundles.</li><li>• Head design provides high tensile strength with very low insertion force.</li><li>• Bent tail ensures a quick and simple installation.</li></ul>
<b>Quantity Per</b>	bag
<b>Product Description</b>	HellermannTyton Heavy-Duty Cable Ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
<b>Short Description</b>	Heavy Duty Cable Tie, 21" Long, UL Rated, 175lb Tensile Strength, POM, Black, 25/pkg

Global Part Name

T150M-POM-BK

Minimum Tensile Strength (Imperial)

175.0

Minimum Tensile Strength (Metric)

780.0

Length L (Imperial)

21.0

Length L (Metric)

530.0

Identification Plate Position

none

Releasable Closure

No

Tie Closure

plastic pawl

Variant

Inside Serrated

Width W (Imperial)

0.35

Width W (Metric)

8.9

Bundle Diameter Min (Imperial)

0.32

Bundle Diameter Min (Metric)

8.0

Bundle Diameter Max (Imperial)

5.9

Bundle Diameter Max (Metric)

150.0

Thickness T (Metric)

1.9

<b>Material</b>	Polyacetal (POM)
<b>Material Shortcut</b>	POM
<b>Flammability</b>	UL 94 HB
<b>Halogen free</b>	Yes
<b>Operating Temperature (Metric)</b>	-40°F to +194°F (-40°C to +90°C)
<b>ROHS Complaint</b>	Yes
<b>Package Quantity(Imperial)</b>	25
<b>Package Quantity (Metric)</b>	25
<b>Customs Number</b>	3926909987