

## Specification Sheet

Part Number: 111-01752



Heavy Duty Cable Tie, 21" Long, UL Rated, 175lb Tensile Strength, PA12, Black, 25/bag

|                     |  |
|---------------------|--|
| Article Number      | 111-01752  |
| Type                | T150M  |
| Color               | Black (BK)   |
| Features & Benefits | <ul style="list-style-type: none"><li>• PA12 cable ties deliver excellent UV, chemical and moisture resistance.</li><li>• Inside serrations provide strong grip on cables and wire bundles.</li><li>• Easy application either manually or with a tensioning tool.</li><li>• Bent tail ensures a quick and simple installation.</li></ul> |
| Quantity Per        | bag  |

**Product Description**

This inside serrated cable tie is manufactured from PA12, which provides excellent UV, chemical and moisture resistance to allow for a longer lifespan in outdoor use. PA12 material absorbs slightly less moisture than PA11, yet is equally resistant to metal oxides. HellermannTyton T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail allows quick and simple installation by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

**Short Description**

Heavy Duty Cable Tie, 21" Long, UL Rated, 175lb Tensile Strength, PA12, Black, 25/bag

**Global Part Name**

T150M-PA12-BK

**Minimum Tensile Strength (Imperial)**

175.0

**Minimum Tensile Strength (Metric)**

780.0

**Length L (Imperial)**

21.0

**Length L (Metric)**

530.0

**Identification Plate Position**

none

**Releasable Closure**

No

**Tie Closure**

plastic pawl

**Variant**

Inside Serrated

**Width W (Imperial)**

0.35

**Width W (Metric)**

8.9

**Bundle Diameter Min (Imperial)**

0.32

**Bundle Diameter Min (Metric)** 8.0

**Bundle Diameter Max (Imperial)** 5.9

**Bundle Diameter Max (Metric)** 150.0

**Thickness T (Metric)** 1.9

**Height H (Imperial)** 14.0

**Height H (Metric)** 355.60

**Cable Tie Width Max (Imperial)** .35

**Cable Tie Width Max (Metric)** 8.9

**Material** Polyamide 12 (PA12)

**Material Shortcut** PA12

**Flammability** UL 94 HB

**Halogen free** Yes

**Operating Temperature (Metric)** -40°F to +203°F (-40°C to +95°C)

**ROHS Complaint** Yes

**Package Quantity(Imperial)** 25

**Package Quantity (Metric)**

25

**Customs Number**

3926909988