

Specification Sheet

Part Number: T18R2HALC2



High-Temp Cable Tie, 4" Long, 14lb Tensile Strength, PAHL, Red, 100/pkg

Article Number	111-01900
Type	T18R
Color	Red (RD)
Features & Benefits	<ul style="list-style-type: none">•Halar cable ties feature a UL 94 V-0 rating to comply with low flame and smoke requirements.•Inside serrations provide strong grip on cables and wire bundles.•Easy application either manually or with a tensioning tool.•Bent tail ensures a quick and simple installation.
Quantity Per	bag

Product Description

The raw material used to manufacture HellermannTyton Halar cable ties is UL 94 V-0 rated. The Halar ties come in a distinct red color for easy identification. T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

Short Description	High-Temp Cable Tie, 4" Long, 14lb Tensile Strength, PAHL, Red, 100/pkg
Global Part Name	T18R-E/CTFE-RD
Minimum Tensile Strength (Imperial)	18.0
Minimum Tensile Strength (Metric)	80.0
Length L (Imperial)	4.0
Length L (Metric)	101.6
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.10
Width W (Metric)	2.5
Bundle Diameter Min (Imperial)	0.06
Bundle Diameter Min (Metric)	1.5
Bundle Diameter Max (Imperial)	0.87
Bundle Diameter Max (Metric)	22.0
Thickness T (Metric)	1.0

Height H (Metric)

3.7

Material

Ethylene Chlorotrifluoroethylene (E/CTFE)

Material Shortcut

E/CTFE

Flammability

UL 94 V0

Operating Temperature (Metric)

-103°F to +302°F (-75°C to +150°C)

ROHS Complaint

Yes

Package Quantity(Imperial)

100

Package Quantity (Metric)

100

Customs Number

3926909987