

Specification Sheet

Part Number: 111-02374



Very high heat resistance up to 200°C (392°F)

PAEK material has double the tensile strength than nylon

PAEK material offers very good chemical resistance against hydrocarbons

High-Temp Cable Tie, 7.9" Long, 100lb Tensile Strength, PAEK, Beige, 1000/pkg

Article Number 111-02374

Type PAT100L

Color Beige (BGE)

Quantity Per bag

Product Description HellermannTyton PAEK cable ties offer very high temperature resistance for use in demanding applications such as in engine compartments, near exhaust, and in enclosed industrial cabinets. The PAEK ties are inside serrated and feature a high performance design that, along with the material, offer extremely high tensile strength for tough applications.

Short Description High-Temp Cable Tie, 7.9" Long, 100lb Tensile Strength, PAEK, Beige, 1000/pkg

Global Part Name	PAT100L-PAEK-BGE
Minimum Tensile Strength (Imperial)	100.0
Minimum Tensile Strength (Metric)	445.0
Length L (Imperial)	7.9
Length L (Metric)	200.7
Width W (Imperial)	0.33
Width W (Metric)	8.0
Bundle Diameter Min (Imperial)	0.06
Bundle Diameter Min (Metric)	1.5
Bundle Diameter Max (Imperial)	2.0
Bundle Diameter Max (Metric)	50.8
Material	Polyaryletherketone (PAEK)
Material Shortcut	PAEK
Flammability	UL 94 V-0

Operating Temperature -67°F to +392°F (-55°C to +200°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Package Quantity (Imperial) 1000

Package Quantity (Metric) 1000

Customs Number 3926909988