


Specification Sheet

Part Number: 111-02447



PVDF Cable Tie, 8" Long, 50lb Tensile Strength, PVDF, Gray, 3000/ctn

Article Number 111-02447

Type T50R

Color Gray (GY)

Features & Benefits

- Made from PVDF for high UV, chemical and thermal resistance.
- Inside serrations deliver secure hold on cable and wire bundles.
- Head design provides high tensile strength with low insertion force.

Quantity Per carton

Product Description

The PVDF cable tie is rated for 25 years' performance outdoors. It provides some of the highest UV, chemical and thermal resistance of any plastic resin. It functions just like our standard ties, simple and fast, streamlining installation and providing reliable performance.

Short Description	PVDF Cable Tie, 8" Long, 50lb Tensile Strength, PVDF, Gray, 3000/ctn
Global Part Name	T50R-PVDF-GY
Minimum Tensile Strength (Imperial)	50.0
Minimum Tensile Strength (Metric)	225.0
Length L (Imperial)	8.0
Length L (Metric)	200.0
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.19
Width W (Metric)	4.7
Bundle Diameter Min (Imperial)	0.31
Bundle Diameter Min (Metric)	8.0
Bundle Diameter Max (Imperial)	1.97

Bundle Diameter Max (Metric)	50.0
Thickness T (Imperial)	0.47
Thickness T (Metric)	1.2
Material	Polyvinylidene Fluoride (PVDF)
Material Shortcut	PVDF
Flammability	UL 94 V0
Operating Temperature (Metric)	-40°F to +284°F (-40°C to +140°C)
ROHS Complaint	Yes
Use Conditions	For Indoor Use Only
Package Quantity(Imperial)	3000
Package Quantity (Metric)	3000
Weight (Metric)	2.49
Weight (Imperial)	0.01

