

## Specification Sheet

Part Number: 111-02496

Flame-retardant cable ties are self-extinguishing and provide low smoke emissions.

Low-profile head with clamping rails provide compact bundling with a full circumferential compression around bundles.

Wider and thinner strap design increases flexibility, provides low insertion and minimizes pinching of bundles.

Bent tail allows for quick insertion into head or mounts.



Wide Strap Cable Tie, 12.1"L, 0.375"–3.25" Bndl Dia, 120lb Tens Stngth, PA66V0, Black, 300/pkg

Article Number 111-02496

Type WSI

Color Black (BK)

Quantity Per bag

Product Description The Heavy Duty Wide-Strap Cable Tie was designed to minimize the pinching of soft bundles and the potential of lateral movement along the bundle. The low-profile head and underside clamping rails increase the grip around the bundle and provide a better fit than traditional cable ties. Can be used in a wide variety of applications where strength is needed.

Short Description	Wide Strap Cable Tie, 12.1"L, 0.375"—3.25" Bndl Dia, 120lb Tens Stngth, PA66V0, Black, 300/pkg
Global Part Name	WSI-PA66V0-BK
Minimum Tensile Strength (Imperial)	120.0
Minimum Tensile Strength (Metric)	535.0
Length L (Imperial)	12.1
Length L (Metric)	307.0
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.5
Width W (Metric)	12.7
Bundle Diameter Min (Imperial)	0.38
Bundle Diameter Min (Metric)	9.5
Bundle Diameter Max (Imperial)	3.25

Bundle Diameter Max (Metric)	82.5
Material	Polyamide 6.6 V0 (PA66V0)
Material Shortcut	PA66V0
Flammability	UL 94 V-0
Halogen Free	Yes
Operating Temperature	-40°F to +212°F (-40°C to +100°C)
ROHS Compliant	Yes
Package Quantity (Imperial)	300
Package Quantity (Metric)	300