

## Specification Sheet

Part Number: T30R1STNLM5

Cable ties made of PA46 material provide a greater resistance to high heat exposures than PA66 heat stabilized material.

Inside serrations allow for strong grip on cables and wire bundles.

Head design provides high tensile strength with very low insertion force.

Bent tail ensures a quick and simple installation.



High-Temp Cable Tie, 6" Long, 30lb Tensile Strength, PA46, Brown, 1000/plain pkg

Article Number 111-03027

Type T30R

Color Brown (BN)

Quantity Per bag

Product Description HellermannTyton standard cable ties feature inside serrations providing a positive hold onto wire and cable bundles. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

Short Description High-Temp Cable Tie, 6" Long, 30lb Tensile Strength, PA46, Brown, 1000/plain pkg

|                                     |                 |
|-------------------------------------|-----------------|
| Global Part Name                    | T30R-PA46-BN    |
| Minimum Tensile Strength (Imperial) | 30              |
| Minimum Tensile Strength (Metric)   | 135             |
| Length L (Imperial)                 | 5.83            |
| Length L (Metric)                   | 148.0           |
| Identification Plate Position       | none            |
| Releasable Closure                  | No              |
| Tie Closure                         | plastic pawl    |
| Variant                             | Inside Serrated |
| Width W (Imperial)                  | 0.14            |
| Width W (Metric)                    | 3.6             |
| Bundle Diameter Min (Imperial)      | 0.06            |
| Bundle Diameter Min (Metric)        | 1.5             |
| Bundle Diameter Max (Imperial)      | 1.38            |
| Bundle Diameter Max (Metric)        | 35.0            |
| Thickness T (Imperial)              | 0.04            |

|                                  |                                   |
|----------------------------------|-----------------------------------|
| Thickness T (Metric)             | 1.1                               |
| Cable Tie Head Length (Imperial) | 0.23                              |
| Cable Tie Head Width (Imperial)  | 0.24                              |
| Height H (Imperial)              | 0.17                              |
| Height H (Metric)                | 4.28                              |
| Material                         | Polyamide 4.6 (PA46)              |
| Material Shortcut                | PA46                              |
| Flammability                     | UL 94 V-2                         |
| Operating Temperature            | -40°F to +266°F (-40°C to +130°C) |
| Reach Compliant (Article 33)     | No                                |
| ROHS Compliant                   | Yes                               |
| Package Quantity (Imperial)      | 1000                              |
| Package Quantity (Metric)        | 1000                              |
| Customs Number                   | 3926909988                        |

## About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 40 countries, with North American headquarters in Milwaukee, Wisconsin. ([www.hellermann.tyton.com](http://www.hellermann.tyton.com)).

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)