


## Specification Sheet

Part Number: T40R9M4



Cable Tie, 8.3" Long, UL Rated, 40lb Tensile Strength, PA66, Natural, 1000/pkg

|                                |  |
|--------------------------------|--|
| <b>Article Number</b>          | 111-04131  |
| <b>Type</b>                    | T40R(U)  |
| <b>Color</b>                   | Natural (NA)   |
| <b>Features &amp; Benefits</b> | <ul style="list-style-type: none"><li>• Engineered and manufactured for maximum performance and quality.</li><li>• Made from 100% high-quality plastic to ensure efficient recycling.</li><li>• Inside serration for a strong grip onto bundles.</li><li>• Easy application either manually or with a tensioning tool.</li><li>• Bent tail allows for simpler insertion.</li></ul> |
| <b>Quantity Per</b>            | bag  |
| <b>Product Description</b>     | T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.                       |

|  |  |
|--|--|
| <b>Short Description</b>                   | Cable Tie, 8.3" Long, UL Rated, 40lb Tensile Strength, PA66, Natural, 1000/pkg |
| <b>Global Part Name</b>                    | T40R(U)-PA66-NA  |
| <b>Minimum Tensile Strength (Imperial)</b> | 40.0   |
| <b>Minimum Tensile Strength (Metric)</b>   | 180.0  |
| <b>Length L (Imperial)</b>                 | 8.3  |
| <b>Length L (Metric)</b>                   | 210.82   |
| <b>Identification Plate Position</b>       | none   |
| <b>Releasable Closure</b>                  | No   |
| <b>Tie Closure</b>                         | plastic pawl   |
| <b>Variant</b>                             | Inside Serrated  |
| <b>Width W (Imperial)</b>                  | 0.16   |
| <b>Width W (Metric)</b>                    | 4.0  |
| <b>Bundle Diameter Min (Imperial)</b>      | 0.06   |
| <b>Bundle Diameter Min (Metric)</b>        | 1.5  |
| <b>Bundle Diameter Max (Imperial)</b>      | 2.2  |
| <b>Bundle Diameter Max (Metric)</b>        | 55.9   |

|  |                                  |
|--|----------------------------------|
| <b>Material</b>                        | Polyamide 6.6 (PA66)             |
| <b>Material Shortcut</b>               | PA66                             |
| <b>Flammability</b>                    | UL 94 V2                         |
| <b>Halogen free</b>                    | Yes                              |
| <b>Operating Temperature (Metric)</b>  | -40°F to +185°F (-40°C to +85°C) |
| <b>ROHS Complaint</b>                  | Yes                              |
| <b>Certification/Specification WEB</b> | UL-ZODZ2.E64139                  |
| <b>UL Recognized (US)</b>              | Yes                              |
| <b>UL Listed (US and Canada)</b>       | Yes                              |
| <b>UL Recognized (US and Canada)</b>   | Yes                              |
| <b>UL Listed (US)</b>                  | Yes                              |
| <b>Package Quantity(Imperial)</b>      | 1000                             |
| <b>Package Quantity (Metric)</b>       | 1000                             |
| <b>Customs Number</b>                  | 3926909988                       |
| <b>Weight (Metric)</b>                 | 0.3                              |

---

© 2019 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)