

Specification Sheet

Part Number: T50R2HALM4



High-Temp Cable Tie, 8" Long, 40lb Tensile Strength, E/CTFE, Red, 1000/pkg

Article Number 111-04897

Type T50R

Color Red (RD)

Features & Benefits

- Halar cable ties feature a UL 94 V-0 rating to comply with low flame and smoke requirements.
- Inside serrations provide strong grip on cables and wire bundles.
- Easy application either manually or with a tensioning tool.
- Bent tail ensures a quick and simple installation.

Quantity Per bag

Product Description	The raw material used to manufacture HellermannTyton Halar cable ties is UL 94 V-0 rated. The Halar ties come in a distinct red color for easy identification. T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.
Short Description	High-Temp Cable Tie, 8" Long, 40lb Tensile Strength, E/CTFE, Red, 1000/pkg
Global Part Name	T50R-E/CTFE-RD
Minimum Tensile Strength (Imperial)	40.0
Minimum Tensile Strength (Metric)	180.0
Length L (Imperial)	8.0
Length L (Metric)	202.0
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.20
Width W (Metric)	5.1

Bundle Diameter Min (Imperial)	0.50
Bundle Diameter Min (Metric)	12.7
Bundle Diameter Max (Imperial)	1.75
Bundle Diameter Max (Metric)	44.5
Thickness T (Metric)	1.2
Material	Ethylene Chlorotrifluoroethylene (E/CTFE)
Material Shortcut	E/CTFE
Flammability	UL 94 V0
Operating Temperature (Metric)	-103°F to +302°F (-75°C to +150°C)
ROHS Complaint	Yes
Use Conditions	For Indoor Use Only
Package Quantity(Imperial)	1000
Package Quantity (Metric)	1000
Customs Number	3926909988

© 2020 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)