

## Specification Sheet

Part Number: T50R0PPM4



Cable Tie, 8" Long, 25lb Tensile Strength, PP, Black, 1000/pkg

**Article Number**

111-04929

**Type**

T50R

**Color**

Black (BK)

**Features & Benefits**

- Polypropylene cable ties deliver excellent resistance to chemicals and salts.
- Inside serrations provide strong grip on cables and wire bundles.
- Easy application either manually or with a tensioning tool.
- Bent tail ensures a quick and simple installation.

**Quantity Per**

bag

**Product Description**

HellermannTyton's polypropylene cable ties offer added resistance to most chemicals. T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

<b>Short Description</b>	Cable Tie, 8" Long, 25lb Tensile Strength, PP, Black, 1000/pkg
<b>Global Part Name</b>	T50R-PP-BK
<b>Minimum Tensile Strength (Imperial)</b>	25.0
<b>Minimum Tensile Strength (Metric)</b>	111.0
<b>Length L (Imperial)</b>	8.0
<b>Length L (Metric)</b>	202.0
<b>Identification Plate Position</b>	none
<b>Releasable Closure</b>	No
<b>Tie Closure</b>	plastic pawl
<b>Variant</b>	Inside Serrated
<b>Width W (Imperial)</b>	0.18
<b>Width W (Metric)</b>	4.6
<b>Bundle Diameter Min (Imperial)</b>	0.06
<b>Bundle Diameter Min (Metric)</b>	1.5
<b>Bundle Diameter Max (Imperial)</b>	1.75
<b>Bundle Diameter Max (Metric)</b>	44.5
<b>Thickness T (Metric)</b>	1.2

<b>Material</b>	Polypropylene (PP)
<b>Material Shortcut</b>	PP
<b>Flammability</b>	UL 94 HB
<b>Halogen free</b>	Yes
<b>Operating Temperature (Metric)</b>	-40°F to +239°F (-40°C to +115°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Package Quantity(Imperial)</b>	1000
<b>Package Quantity (Metric)</b>	1000
<b>Customs Number</b>	3926909987
<b>Content Unit(BMEcat)</b>	pcs.