

## Specification Sheet

Part Number: T50R9PPC2



Cable Tie, 8" Long, 25lb Tensile Strength, PP, Natural, 100/pkg

**Article Number**

111-04931

**Type**

T50R

**Color**

Natural (NA)

**Features & Benefits**

- Polypropylene cable ties deliver excellent resistance to chemicals and salts.
- Inside serrations provide strong grip on cables and wire bundles.
- Easy application either manually or with a tensioning tool.
- Bent tail ensures a quick and simple installation.

**Quantity Per**

bag

**Product Description**

HellermannTyton's polypropylene cable ties offer added resistance to most chemicals. T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

<b>Short Description</b>	Cable Tie, 8" Long, 25lb Tensile Strength, PP, Natural, 100/pkg
<b>Global Part Name</b>	T50R-PP-NA
<b>Minimum Tensile Strength (Imperial)</b>	25.0
<b>Minimum Tensile Strength (Metric)</b>	111.0
<b>Length L (Imperial)</b>	8.0
<b>Length L (Metric)</b>	203.2
<b>Identification Plate Position</b>	none
<b>Releasable Closure</b>	No
<b>Tie Closure</b>	plastic pawl
<b>Variant</b>	Inside Serrated
<b>Width W (Imperial)</b>	0.18
<b>Width W (Metric)</b>	4.6
<b>Bundle Diameter Min (Imperial)</b>	0.06
<b>Bundle Diameter Min (Metric)</b>	1.5
<b>Bundle Diameter Max (Imperial)</b>	1.75
<b>Bundle Diameter Max (Metric)</b>	44.5
<b>Thickness T (Imperial)</b>	0.05

**Thickness T (Metric)** 1.2

**Material** Polypropylene (PP)

**Material Shortcut** PP

**Flammability** UL 94 HB

**Halogen free** Yes

**Operating Temperature (Metric)** -40°F to +239°F (-40°C to +115°C)

**Reach Complaint(Article 33)** Yes

**ROHS Complaint** Yes

**Package Quantity(Imperial)** 100

**Package Quantity (Metric)** 100

**Customs Number** 3926909988

**Content Unit(BMEcat)** pcs.

