

Specification Sheet

Part Number: T120R0PPH4



Cable Tie, 15.2" Long, 60lb Tensile Strength, PP, Black, 500/pkg

Article Number

111-12066

Type

T120R

Color

Black (BK)

Features & Benefits

- Polypropylene cable ties deliver excellent resistance to chemicals and salts.
- Inside serrations provide strong grip on cables and wire bundles.
- Easy application either manually or with a tensioning tool.
- Bent tail ensures a quick and simple installation.

Quantity Per

bag

Product Description

HellermannTyton's polypropylene cable ties offer added resistance to most chemicals. T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

Short Description	Cable Tie, 15.2" Long, 60lb Tensile Strength, PP, Black, 500/pkg
Global Part Name	T120R-PP-BK
Minimum Tensile Strength (Imperial)	60.0
Minimum Tensile Strength (Metric)	267.0
Length L (Imperial)	15.2
Length L (Metric)	387.0
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.30
Width W (Metric)	7.6
Bundle Diameter Min (Imperial)	0.20
Bundle Diameter Min (Metric)	5.0
Bundle Diameter Max (Imperial)	4.1
Bundle Diameter Max (Metric)	104.1
Thickness T (Imperial)	0.07

Thickness T (Metric) 1.8

Material Polypropylene (PP)

Material Shortcut PP

Flammability UL 94 HB

Halogen free Yes

Operating Temperature (Metric) -40°F to +239°F (-40°C to +115°C)

Reach Complaint(Article 33) Yes

ROHS Complaint Yes

Package Quantity(Imperial) 500

Package Quantity (Metric) 500

Customs Number 3926909988

Content Unit(BMEcat) pcs.

Weight (Metric) 5.2

