

Specification Sheet

Part Number: 111-12300



Wide Strap Cable Tie, 9.1"L, 0.375"-2.25" Bundle Dia, 120lb Tens Stngth, PA66HIRHSUV, Black, 300/pkg

| | |
|---------------------|--|
| Article Number | 111-12300 |
| Type | WSS |
| Color | Black (BK) |
| Features & Benefits | <ul style="list-style-type: none">•Wide strap is designed to minimize pinching of soft hoses and convoluted tubing.•Low-profile head with clamping rails provide compact bundling with a full circumferential compression around bundles.•Wider and thinner strap design increases flexibility, provides low insertion and minimizes pinching of bundles.•Bent tail allows for quick insertion into head or mounts. |
| Quantity Per | bag |

Product Description

The Heavy Duty Wide-Strap Cable Tie was designed to minimize the pinching of soft bundles and the potential of lateral movement along the bundle. The low-profile head and underside clamping rails increase the grip around the bundle and provide a better fit than traditional cable ties. These are used primarily in the trucking and heavy equipment industries, but can be used in a wide variety of applications where strength is needed.

| | |
|--|--|
| Short Description | Wide Strap Cable Tie, 9.1"L, 0.375"-2.25" Bundle Dia, 120lb Tens Stngth, PA66HIRHSUV, Black, 300/pkg |
| Global Part Name | WSS-PA66HIRHSUV-BK |
| Minimum Tensile Strength (Imperial) | 120 |
| Minimum Tensile Strength (Metric) | 535 |
| Length L (Imperial) | 9.1 |
| Length L (Metric) | 230.0 |
| Identification Plate Position | none |
| Releasable Closure | No |
| Tie Closure | plastic pawl |
| Variant | Inside Serrated |
| Width W (Imperial) | 0.5 |
| Width W (Metric) | 12.7 |
| Bundle Diameter Min (Imperial) | 0.375 |
| Bundle Diameter Min (Metric) | 9.7 |
| Bundle Diameter Max (Imperial) | 2.2 |
| Bundle Diameter Max (Metric) | 58.4 |

Thickness T (Imperial)

0.055

Thickness T (Metric)

1.4

Cable Tie Head Length (Imperial)

0.393

Cable Tie Head Width (Imperial)

0.78

Material

Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

Material Shortcut

PA66HIRHSUV

Flammability

UL 94 HB

Operating Temperature (Metric)

-40°F to +230°F (-40°C to +110°C)

Reach Complaint(Article 33)

Yes

ROHS Complaint

Yes

Package Quantity(Imperial)

300

Package Quantity (Metric)

300

Customs Number

3926909987

Content Unit(BMEcat)

pcs.

Weight (Metric)

0.0042

Weight (Imperial)

0.0092

© 2019 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)