

## Specification Sheet

Part Number: T150XL0X2



Engineered and manufactured for maximum performance and quality.

Made from 100% high-quality plastic to ensure efficient recycling.

Inside serration for a strong grip onto bundles.

Easy application either manually or with a tensioning tool.

Heavy Duty Cable Tie, 43" Long, UL Rated, 175lb Tensile Strength, PA66, Black, 25/pkg

Article Number 111-15500

Type T150XL

Color Black (BK)

Quantity Per bag

Product Description Heavy duty T-Series cable ties feature inside serrations to provide a positive hold on wire and cable bundles. Durable head design guarantees high tensile strength and a low insertion force. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

Short Description Heavy Duty Cable Tie, 43" Long, UL Rated, 175lb Tensile Strength, PA66, Black, 25/pkg

|                                     |                 |
|-------------------------------------|-----------------|
| Global Part Name                    | T150XL-PA66-BK  |
| Minimum Tensile Strength (Imperial) | 175             |
| Minimum Tensile Strength (Metric)   | 780             |
| Length L (Imperial)                 | 43.0            |
| Length L (Metric)                   | 1095.0          |
| Identification Plate Position       | none            |
| Releasable Closure                  | No              |
| Tie Closure                         | plastic pawl    |
| Variant                             | Inside Serrated |
| Width W (Imperial)                  | 0.35            |
| Width W (Metric)                    | 8.9             |
| Bundle Diameter Min (Imperial)      | 6.0             |
| Bundle Diameter Min (Metric)        | 152.0           |
| Bundle Diameter Max (Imperial)      | 13.0            |
| Bundle Diameter Max (Metric)        | 330.0           |
| Thickness T (Imperial)              | 0.083           |

|                               |  |
|-------------------------------|--|
| Thickness T (Metric)          | 2.1  |
| Material                      | Polyamide 6.6 (PA66)                                   |
| Material Shortcut             | PA66   |
| Flammability                  | UL 94 V-2  |
| Halogen Free                  | Yes  |
| UV Resistant (Yes/No)         | No   |
| Operating Temperature         | -40°F to +185°F (-40°C to +85°C)                       |
| Reach Compliant (Article 33)  | Yes  |
| ROHS Compliant                | Yes  |
| Certification/Specification   | UL   ANSI/UL 746B UL   ANSI/UL 1565 UL   ANSI/UL 62275 |
| UL Recognized (US)            | Yes  |
| UL Recognized (US and Canada) | Yes  |
| Package Quantity (Imperial)   | 25   |
| Package Quantity (Metric)     | 25   |
| Customs Number                | 3926909988   |

## About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 40 countries, with North American headquarters in Milwaukee, Wisconsin. ([www.hellermann.tyton.com](http://www.hellermann.tyton.com)).

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)