

## Specification Sheet

Part Number: TELS-H



Extended-Length Tie Heads, POM, Black, 25/pkg

**Article Number**

111-31000

**Type**

EL-TY (TELSH)

**Color**

Black (BK)

**Features & Benefits**

- Continuous strap and separate heads allow for any bundle diameter, eliminating waste.
- Smooth strap prevents cable damage.
- UV resistant materials contain an inhibitor which prolongs the life of the tie in outdoor environments.

**Quantity Per**

bag

**Product Description**

Extended Length Ties provide a high tensile strength strapping system consisting of a continuous strap and separate locking head making it suitable for any bundle diameter, eliminating waste. The smooth strap and specially designed heads with stainless steel pawls provide a strong grip on cables and wires without damage during vibration or in extreme environments. Spacers are available for dual bundle applications.

|  |   |
|--|---|
| <b>Short Description</b>                   | Extended-Length Tie Heads, POM, Black, 25/pkg |
| <b>Global Part Name</b>                    | EL-TY (TELSH)-POM-BK                          |
| <b>Minimum Tensile Strength (Imperial)</b> | 250.0   |
| <b>Length L (Imperial)</b>                 | 0.62  |
| <b>Length L (Metric)</b>                   | 15.75   |
| <b>Fixation Method</b>                     | 2 piece                                       |
| <b>Identification Plate Position</b>       | none  |
| <b>Releasable Closure</b>                  | No  |
| <b>Tie Closure</b>                         | steel pawl                                    |
| <b>Variant</b>                             | Extended Length                               |
| <b>Width W (Imperial)</b>                  | 0.8   |
| <b>Width W (Metric)</b>                    | 20.3  |
| <b>Height H (Imperial)</b>                 | .49   |
| <b>Height H (Metric)</b>                   | 12.40   |
| <b>Cable Tie Width Max (Metric)</b>        | 12.7  |

|                                       |                                  |
|---------------------------------------|----------------------------------|
| <b>Material</b>                       | Polyacetal (POM)                 |
| <b>Material Shortcut</b>              | POM                              |
| <b>Material Cable Tie</b>             | Polyacetal (POM)                 |
| <b>Material Head</b>                  | Polyacetal (POM)                 |
| <b>Flammability</b>                   | UL 94 HB                         |
| <b>Operating Temperature (Metric)</b> | -40°F to +185°F (-40°C to +85°C) |
| <b>Reach Complaint(Article 33)</b>    | Yes                              |
| <b>ROHS Complaint</b>                 | Yes                              |
| <b>Package Quantity(Imperial)</b>     | 25                               |
| <b>Package Quantity (Metric)</b>      | 25                               |
| <b>Customs Number</b>                 | 3926909987                       |
| <b>Content Unit(BMEcat)</b>           | pcs.                             |
| <b>Weight (Metric)</b>                | 1.2                              |