

## Specification Sheet

Part Number: TELS-SPK2



Continuous strap and separate heads allow for any bundle diameter, eliminating waste.

Smooth strap prevents cable damage.

Extended-Length Tie Spacer, PP, Black, 50/pkg

Article Number 111-32000

Type EL-TY (TELS-SPK2)

Color Black (BK)

Quantity Per bag

Product Description Extended Length Ties provide a high tensile strength strapping system consisting of a continuous strap and separate locking head making it suitable for any bundle diameter, eliminating waste. The smooth strap and specially designed heads with stainless steel pawls provide a strong grip on cables and wires without damage during vibration or in extreme environments. Spacers are available for dual bundle applications.

Short Description Extended-Length Tie Spacer, PP, Black, 50/pkg

|                                     |                         |
|-------------------------------------|-------------------------|
| Global Part Name                    | EL-TY (TELS-SPK2)-PP-BK |
| Contents of pkg/kit                 | 50 Spacer               |
| Minimum Tensile Strength (Imperial) | 250                     |
| Minimum Tensile Strength (Metric)   | 1115                    |
| Length L (Imperial)                 | 1.2                     |
| Length L (Metric)                   | 30.5                    |
| Fixation Method                     | 2 piece                 |
| Identification Plate Position       | none                    |
| Releasable Closure                  | No                      |
| Tie Closure                         | steel pawl              |
| Variant                             | Endless                 |
| Width W (Imperial)                  | 2.1                     |
| Width W (Metric)                    | 53.3                    |
| Height H (Imperial)                 | 0.67                    |
| Height H (Metric)                   | 17.0                    |
| Cable Tie Width Max (Metric)        | 12.7                    |

|                              |  |
|------------------------------|--|
| Material                     | Polypropylene (PP)   |
| Material Shortcut            | PP   |
| Material Head                | Polyacetal, UV stabilized (POMUV) with stainless steel pawl (SS) |
| Flammability                 | UL 94 HB   |
| UV Resistant (Yes/No)        | No   |
| Operating Temperature        | -40°F to +239°F (-40°C to +115°C)                                |
| Reach Compliant (Article 33) | Yes  |
| ROHS Compliant               | Yes  |
| Package Quantity (Imperial)  | 50   |
| Package Quantity (Metric)    | 50   |
| Customs Number               | 3926909988   |

## About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 40 countries, with North American headquarters in Milwaukee, Wisconsin. ([www.hellermann.tyton.com](http://www.hellermann.tyton.com)).

