

Specification Sheet

Part Number: TELS-SPK2

Spacers provide distance between two bundles.

Continuous strap and separate heads allow for any bundle diameter, eliminating waste.

Smooth strap prevents cable damage.

UV resistant materials contain an inhibitor which prolongs the life of the tie in outdoor environments.



Extended-Length Tie Spacer, PP, Black, 50/pkg

Article Number 111-32000

Type EL-TY (TELS-SPK2)

Color Black (BK)

Quantity Per bag

Product Description Extended Length Ties provide a high tensile strength strapping system consisting of a continuous strap and separate locking head making it suitable for any bundle diameter, eliminating waste. The smooth strap and specially designed heads with stainless steel pawls provide a strong grip on cables and wires without damage during vibration or in extreme environments. Spacers are available for dual bundle applications.

Short Description	Extended-Length Tie Spacer, PP, Black, 50/pkg
Global Part Name	EL-TY (TELS-SPK2)-PP-BK
Contents of pkg/kit	50 Spacer
Minimum Tensile Strength (Imperial)	250.0
Minimum Tensile Strength (Metric)	1115.0
Length L (Imperial)	1.2
Length L (Metric)	30.5
Fixation Method	2 piece
Identification Plate Position	none
Releasable Closure	No
Tie Closure	steel pawl
Variant	Extended Length
Width W (Imperial)	2.1
Width W (Metric)	53.3
Height H (Imperial)	0.67
Height H (Metric)	17.0

Cable Tie Width Max (Metric)	12.7
Material	Polypropylene (PP)
Material Shortcut	PP
Material Head	Polyacetal, UV stabilized (POMUV) with stainless steel pawl (SS)
Flammability	UL 94 HB
Operating Temperature	-40°F to +239°F (-40°C to +115°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	50
Package Quantity (Metric)	50
Customs Number	3926909988