

Specification Sheet

Part Number: TELS-SPOOL



Continuous strap and separate heads allow for any bundle diameter, eliminating waste.

Smooth strap prevents cable damage.

UV resistant materials contain an inhibitor which prolongs the life of the tie in outdoor environments.

Extended-Length Tie, POM, Black, 1-50 ft reel of strap/pkg

| | |
|-----------------------|------------|
| Article Number | 111-32106 |
| Type | TELS-SPOOL |
| Color | Black (BK) |
| Quantity Per | reel |

| | |
|----------------------------|--|
| Product Description | Extended Length Ties provide a high tensile strength strapping system consisting of a continuous strap and separate locking head making it suitable for any bundle diameter, eliminating waste. The smooth strap and specially designed heads with stainless steel pawls provide a strong grip on cables and wires without damage during vibration or in extreme environments. Spacers are available for dual bundle applications. |
|----------------------------|--|

| | |
|--------------------------|--|
| Short Description | Extended-Length Tie, POM, Black, 1-50 ft reel of strap/pkg |
|--------------------------|--|

Global Part Name TELS-SPOOL-POM-BK

Minimum Tensile Strength (Imperial) 250.0

Minimum Tensile Strength (Metric) 1115.0

Length L (Imperial) 50.0

Length L (Metric) 15.2

Fixation Method 2 piece

Identification Plate Position none

Releasable Closure No

Tie Closure steel pawl

Variant Extended Length

Width W (Imperial) 0.5

Width W (Metric) 12.8

Thickness T (Imperial) 0.06

Thickness T (Metric) 1.52

| | |
|-------------------------------------|----------------------------------|
| Material | Polyacetal (POM) |
| Material Shortcut | POM |
| Material Cable Tie | Polyacetal (POM) |
| Material Head | Polyacetal (POM) |
| Flammability | UL 94 HB |
| Operating Temperature | -40°F to +194°F (-40°C to +90°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Package Quantity (Imperial) | 1 |
| Package Quantity (Metric) | 1 |
| Customs Number | 3926909988 |