

## Specification Sheet

Part Number: 111-85395



Arrowhead design makes installation by hand quick and easy without the need for tools.

Ties "clicks" into place upon final installation signaling installer insertion is complete.

Design provides low insertion and high extraction force.

1-Pc Cable Tie/Arrowhead Mount w/Wings, 5.3"L, 50lb Tensile, PA66HIRHS, Gray, 500/bag

Article Number 111-85395

Type T50SSL5

Color Gray (GY)

Quantity Per bag

Product Description Arrowhead Push Ties secure fast and easy, while providing a disc feature to minimize the ingress of dust, dirt, and water. The anchor adjusts for variations in panel thicknesses which insures a secure fixing at all times.

Short Description 1-Pc Cable Tie/Arrowhead Mount w/Wings, 5.3"L, 50lb Tensile, PA66HIRHS, Gray, 500/bag

Global Part Name T50SSL5-PA46-GY

Minimum Tensile Strength (Imperial)	50.0
Minimum Tensile Strength (Metric)	225
Length L (Imperial)	5.3
Length L (Metric)	135
Fixation Method	Arrowhead
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.181
Width W (Metric)	4.6
Bundle Diameter Min (Imperial)	0.06
Bundle Diameter Min (Metric)	1.5
Bundle Diameter Max (Imperial)	1.0
Bundle Diameter Max (Metric)	27.0
Height H (Imperial)	0.4

Height H (Metric)	10
Panel Thickness Min (Imperial)	0.019
Panel Thickness Max (Imperial)	0.11
Panel Thickness Min (Metric)	0.5
Panel Thickness Max (Metric)	2.7
Mounting Hole Diameter D (Imperial)	0.24 - 0.26
Mounting Hole Diameter D (Metric)	6.1 - 6.5 mm
Mounting Hole Diameter D Min (Imperial)	0.24
Mounting Hole Diameter D Max (Imperial)	0.26
Mounting Hole Diameter D Max (Metric)	6.5
Disc Diameter (Metric)	16.26
Disc Diameter (Imperial)	0.64
Material	Polyamide 4.6 (PA46)
Material Shortcut	PA46
Flammability	UL 94 V-2

Operating Temperature	-40°F to +302°F (-40°C to +150°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	1000
Package Quantity (Metric)	1000
Customs Number	3926909988

## About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. ([www.hellermann.tyton.com](http://www.hellermann.tyton.com)).

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)