

Specification Sheet

Part Number: T50SL6.NN6P



Wing design helps stabilize the tie in high vibration applications
Includes a ladder type strap as opposed to a conventional serrated strap;
providing the benefit of being extra flexible.

Design of tie provides low insertion and high extraction force.

1-Pc Cable Tie/Arrowhead Mount w/Wings, 6.5"L, 50lb, 0.25 - 0.3" Hole Dia, PA66, Natural, 500/bag

Article Number 111-85469

Type T50SL6

Color Natural (NA)

Quantity Per bag

Product Description Wing design helps stabilize the tie in high vibration applications. One-piece mounting ties offer a complete solution by both bundling cable and simultaneously providing a mounting solution. HellermannTyton's one-piece mounting ties offer the ideal combination of high specification materials and superior design to suit the mounting and bundling needs of complex applications.

Short Description 1-Pc Cable Tie/Arrowhead Mount w/Wings, 6.5"L, 50lb, 0.25 - 0.3" Hole Dia, PA66, Natural, 500/bag

Global Part Name T50SL6-PA66-NA

Minimum Tensile Strength (Imperial) 50.0

Minimum Tensile Strength (Metric) 225

Length L (Imperial) 6.5

Length L (Metric) 165

Fixation Method Arrowhead

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.18

Width W (Metric) 4.6

Bundle Diameter Min (Imperial) 0.06

Bundle Diameter Min (Metric) 1.5

Bundle Diameter Max (Imperial) 1.3

Bundle Diameter Max (Metric) 34.0

| | |
|---|--------------|
| Thickness T (Imperial) | 0.05 |
| Thickness T (Metric) | 1.2 |
| Panel Thickness Min (Imperial) | 0.019 |
| Panel Thickness Max (Imperial) | 0.098 |
| Panel Thickness Min (Metric) | 0.5 |
| Panel Thickness Max (Metric) | 2.5 |
| Mounting Hole Diameter D (Imperial) | 0.25 - 0.3 |
| Mounting Hole Diameter D (Metric) | 6.3 - 7.5 mm |
| Mounting Hole Diameter D Min (Imperial) | 0.25 |
| Mounting Hole Diameter D Max (Imperial) | 0.3 |
| Mounting Hole Diameter D Max (Metric) | 7.5 |
| Disc Diameter (Metric) | 18.5 |
| Disc Diameter (Imperial) | 0.73 |

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

| | |
|-----------------------------|----------------------------------|
| Flammability | UL 94 V-2 |
| Operating Temperature | -40°F to +185°F (-40°C to +85°C) |
| ROHS Compliant | Yes |
| Package Quantity (Imperial) | 500 |
| Package Quantity (Metric) | 500 |
| Customs Number | 3926909988 |

© 2022 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)