

Specification Sheet

Part Number: T50SL7.NN6P



1-Pc Cable Tie/Arrowhead Mount w/Wings, 6.5"L, 50lb, 0.27 - 0.28" Hole Dia, PA66, Natural, 500/bag

Article Number 111-85479

Type T50SL7

Color Natural (NA)

Features & Benefits

- Two piece assembly allows the mount to slide along the strap ensuring proper orientation.
- Arrowhead style mount provides low insertion and high extraction force.
- Arrowhead disc protects against dirt and other impurities.

Quantity Per bag

Product Description	Wing design helps stabilize the tie in high vibration applications. One-piece mounting ties offer a complete solution by both bundling cable and simultaneously providing a mounting solution. HellermannTyton's one-piece mounting ties offer the ideal combination of high specification materials and superior design to suit the mounting and bundling needs of complex applications.
Short Description	1-Pc Cable Tie/Arrowhead Mount w/Wings, 6.5"L, 50lb, 0.27 - 0.28" Hole Dia, PA66, Natural, 500/bag
Global Part Name	T50SL7-PA66-NA
Minimum Tensile Strength (Imperial)	50.0
Minimum Tensile Strength (Metric)	225
Length L (Imperial)	6.5
Length L (Metric)	165
Fixation Method	Arrowhead
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.18
Width W (Metric)	4.6

Bundle Diameter Min (Imperial)	0.06
Bundle Diameter Min (Metric)	1.5
Bundle Diameter Max (Imperial)	1.3
Bundle Diameter Max (Metric)	34.0
Thickness T (Imperial)	0.05
Thickness T (Metric)	1.2
Height H (Imperial)	0.4
Height H (Metric)	10.0
Panel Thickness Min(Imperial)	0.031
Panel Thickness Max(Imperial)	0.098
Panel Thickness Min (Metric)	0.8
Panel Thickness Max (Metric)	2.5
Mounting Hole Diameter D (Imperial)	0.27 - 0.28
Mounting Hole Diameter D (Metric)	6.9 - 7.1 mm
Mounting Hole Diameter D Min (Imperial)	0.27
Mounting Hole Diameter D Max (Imperial)	0.28
Mounting Hole Diameter D Max (Metric)	7.1

Disc Diameter (Imperial)	0.73
Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Flammability	UL 94 V2
Operating Temperature (Metric)	-40°F to +185°F (-40°C to +85°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	500
Package Quantity (Metric)	500
Customs Number	3926909988
Content Unit(BMEcat)	pcs.
Weight (Metric)	3.2

