

## Specification Sheet

Part Number: T50SL7.NN6P



1-Piece Cable Tie/Arrowhead Mount with Wings, 6.5"L, 50lb, 0.27 - 0.28" Mtg Hole, PA66, Natural, 500/bag

Article Number	111-85479
Type	T50SL7
Color	Natural (NA)
Features & Benefits	<ul style="list-style-type: none"><li>•Two piece assembly allows the mount to slide along the strap ensuring proper orientation.</li><li>•Arrowhead style mount provides low insertion and high extraction force.</li><li>•Arrowhead disc protects against dirt and other impurities.</li></ul>
Quantity Per	bag

### Product Description

Wing design helps stabilize the tie in high vibration applications. One-piece mounting ties offer a complete solution by both bundling cable and simultaneously providing a mounting solution. HellermannTyton's one-piece mounting ties offer the ideal combination of high specification materials and superior design to suit the mounting and bundling needs of complex applications.

**Short Description**

1-Piece Cable Tie/Arrowhead Mount with Wings, 6.5"L, 50lb, 0.27 - 0.28" Mtg Hole, PA66, Natural, 500/bag

**Global Part Name**

T50SL7-PA66-NA

**Minimum Tensile Strength (Imperial)**

50.0

**Minimum Tensile Strength (Metric)**

225

**Length L (Imperial)**

6.5

**Length L (Metric)**

165

**Fixation Method**

Arrowhead

**Identification Plate Position**

none

**Releasable Closure**

No

**Tie Closure**

plastic pawl

**Variant**

Inside Serrated

**Width W (Imperial)**

0.18

**Width W (Metric)**

4.6

**Bundle Diameter Min (Imperial)**

0.06

**Bundle Diameter Min (Metric)**

1.5

**Bundle Diameter Max (Imperial)**

1.3

<b>Bundle Diameter Max (Metric)</b>	34.0
<b>Thickness T (Imperial)</b>	0.05
<b>Thickness T (Metric)</b>	1.2
<b>Height H (Imperial)</b>	0.4
<b>Height H (Metric)</b>	10.0
<b>Panel Thickness Min(Imperial)</b>	0.031
<b>Panel Thickness Max(Imperial)</b>	0.098
<b>Panel Thickness Min (Metric)</b>	0.8
<b>Panel Thickness Max (Metric)</b>	2.5
<b>Mounting Hole Diameter D (Imperial)</b>	0.27 - 0.28
<b>Mounting Hole Diameter D (Metric)</b>	6.9 - 7.1 mm
<b>Mounting Hole Diameter D Min (Imperial)</b>	0.27
<b>Mounting Hole Diameter D Max (Imperial)</b>	0.28
<b>Mounting Hole Diameter D Max (Metric)</b>	7.1
<b>Disc Diameter (Imperial)</b>	0.73
<b>Material</b>	Polyamide 6.6 (PA66)

**Material Shortcut**

PA66

**Flammability**

UL 94 V2

**Operating Temperature (Metric)**

-40°F to +185°F (-40°C to +85°C)

**Reach Complaint(Article 33)**

Yes

**ROHS Complaint**

Yes

**Package Quantity(Imperial)**

500

**Package Quantity (Metric)**

500

**Customs Number**

3926909987

**Content Unit(BMEcat)**

pcs.

**Weight (Metric)**

3.2