

## Specification Sheet

Part Number: 111-85560



1-Piece Cable Tie/Arrowhead Mount with Wings, 4"L, 18lb, 0.18 - 0.19" Mtg Hole, PA66UV, Black, 100/bag

**Article Number** 111-85560

**Type** T18RSF

**Color** Black (BK)

**Features & Benefits**

- Wing design helps stabilize the tie in high vibration applications.
- Includes a ladder type strap as opposed to a conventional serrated strap, providing the benefit of being extra flexible.
- Wing design provides low insertion and high extraction force.

**Quantity Per** bag

<b>Product Description</b>	One-piece mounting ties offer a complete solution by both bundling cable and simultaneously providing a mounting solution. Wing design helps stabilize the tie in high vibration applications. HellermannTyton's one-piece mounting ties offer the ideal combination of high specification materials and superior design to suit the mounting and bundling needs of complex applications.
<b>Short Description</b>	1-Piece Cable Tie/Arrowhead Mount with Wings, 4"L, 18lb, 0.18 - 0.19" Mtg Hole, PA66UV, Black, 100/bag
<b>Global Part Name</b>	T18RSF-PA66UV-BK
<b>Minimum Tensile Strength (Imperial)</b>	18.0
<b>Minimum Tensile Strength (Metric)</b>	80
<b>Length L (Imperial)</b>	4.0
<b>Length L (Metric)</b>	100
<b>Fixation Method</b>	Arrowhead
<b>Identification Plate Position</b>	none
<b>Releasable Closure</b>	No
<b>Tie Closure</b>	plastic pawl
<b>Variant</b>	Inside Serrated
<b>Width W (Imperial)</b>	0.1
<b>Width W (Metric)</b>	2.5

<b>Bundle Diameter Min (Imperial)</b>	0.06
<b>Bundle Diameter Min (Metric)</b>	1.5
<b>Bundle Diameter Max (Imperial)</b>	0.6
<b>Bundle Diameter Max (Metric)</b>	16.0
<b>Thickness T (Imperial)</b>	0.039
<b>Thickness T (Metric)</b>	1.0
<b>Panel Thickness Min (Imperial)</b>	0.031
<b>Panel Thickness Max (Imperial)</b>	0.12
<b>Panel Thickness Min (Metric)</b>	0.8
<b>Panel Thickness Max (Metric)</b>	3.0
<b>Mounting Hole Diameter D (Imperial)</b>	0.18 - 0.19
<b>Mounting Hole Diameter D (Metric)</b>	4.6 - 4.8 mm
<b>Mounting Hole Diameter D Min (Imperial)</b>	0.177
<b>Mounting Hole Diameter D Max (Imperial)</b>	0.19
<b>Mounting Hole Diameter D Max (Metric)</b>	4.85

<b>Material</b>	Polyamide 6.6 UV-stabilized (PA66UV)
<b>Material Shortcut</b>	PA66UV
<b>Material Cable Tie</b>	Polyamide 6.6 UV-resistant (PA66UV)
<b>Flammability</b>	UL 94 V2
<b>Operating Temperature</b>	-40°F to +185°F (-40°C to +85°C)
<b>Reach Compliant (Article 33)</b>	Yes
<b>ROHS Compliant</b>	Yes
<b>Package Quantity (Imperial)</b>	100
<b>Package Quantity (Metric)</b>	100
<b>Customs Number</b>	3926909988
<b>Weight (Metric)</b>	0.3