

Specification Sheet

Part Number: 111-85560



1-Piece Cable Tie/Arrowhead Mount with Wings, 4"L, 18lb, 0.18 - 0.19" Mtg Hole, PA66UV, Black, 100/bag

Article Number	111-85560
Type	T18RSF
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none">•Two piece assembly allows the mount to slide along the strap ensuring proper orientation.•Arrowhead style mount provides low insertion and high extraction force.•Arrowhead disc protects against dirt and other impurities.
Quantity Per	bag

Product Description

Wing design helps stabilize the tie in high vibration applications. One-piece mounting ties offer a complete solution by both bundling cable and simultaneously providing a mounting solution. HellermannTyton's one-piece mounting ties offer the ideal combination of high specification materials and superior design to suit the mounting and bundling needs of complex applications.

Short Description	1-Piece Cable Tie/Arrowhead Mount with Wings, 4"L, 18lb, 0.18 - 0.19" Mtg Hole, PA66UV, Black, 100/bag
Global Part Name	T18RSF-PA66UV-BK
Minimum Tensile Strength (Imperial)	18.0
Minimum Tensile Strength (Metric)	80
Length L (Imperial)	4.0
Length L (Metric)	100
Fixation Method	Arrowhead
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.1
Width W (Metric)	2.5
Bundle Diameter Min (Imperial)	0.06
Bundle Diameter Min (Metric)	1.5
Bundle Diameter Max (Imperial)	0.6

Bundle Diameter Max (Metric)	16.0
Thickness T (Imperial)	0.039
Thickness T (Metric)	1.0
Panel Thickness Min(Imperial)	0.031
Panel Thickness Max(Imperial)	0.12
Panel Thickness Min (Metric)	0.8
Panel Thickness Max (Metric)	3.0
Mounting Hole Diameter D (Imperial)	0.18 - 0.19
Mounting Hole Diameter D (Metric)	4.6 - 4.8 mm
Mounting Hole Diameter D Min (Imperial)	0.177
Mounting Hole Diameter D Max (Imperial)	0.19
Mounting Hole Diameter D Max (Metric)	4.85
Material	Polyamide 6.6 UV-resistant (PA66UV)
Material Shortcut	PA66UV
Material Cable Tie	Polyamide 6.6 UV-resistant (PA66UV)
Flammability	UL 94 V2

Operating Temperature (Metric)	-40°F to +185°F (-40°C to +85°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	100
Package Quantity (Metric)	100
Customs Number	3926909987
Content Unit(BMEcat)	pcs.
Weight (Metric)	0.3