

Specification Sheet

Part Number: MBT5S-S



Stainless Steel Tie, 5" Long, 202lb Tensile Strength, SS304, Metal, 100/pkg

Article Number	111-93058
Type	MBT5SS
Color	Metal (ML)
Features & Benefits	<ul style="list-style-type: none">• 304 grade stainless steel offers excellent resistance to corrosion, weather and chemical resistance.• Self locking, ball bearing mechanism assures high tensile strength and easy insertion.• Fully enclosed head does not allow dirt or grit to interfere with locking mechanism.• High tensile strength for dependability and safety on heavy duty applications.
Quantity Per	bag
Product Description	HellermannTyton's stainless steel ties are designed with a ball bearing locking mechanism to assure high tensile strength and easy insertion when securing hoses, cables, pipes and more. Available in 304 or 316 grades of stainless steel, providing protection when used in corrosive environments, fire resistance and temperature extremes.

Short Description	Stainless Steel Tie, 5" Long, 202lb Tensile Strength, SS304, Metal, 100/pkg
Global Part Name	MBT5SS-SS304-ML
Minimum Tensile Strength (Imperial)	202.0
Minimum Tensile Strength (Metric)	900.0
Length L (Imperial)	5.0
Length L (Metric)	127.0
Identification Plate Position	none
Releasable Closure	No
Tie Closure	ball bearing lock
Variant	No Serration
Width W (Imperial)	0.18
Width W (Metric)	4.6
Bundle Diameter Min (Imperial)	0.47
Bundle Diameter Min (Metric)	12.0
Bundle Diameter Max (Imperial)	0.98
Bundle Diameter Max (Metric)	25.0
Thickness T (Imperial)	0.01

Thickness T (Metric) 0.3

Material Stainless Steel (SS304)

Material Shortcut SS304

Flammability Non-Burning

Halogen free Yes

Operating Temperature (Metric) -112°F to +1000°F (-80°C to +538°C)

Reach Complaint(Article 33) Yes

ROHS Complaint Yes

Package Quantity(Imperial) 100

Package Quantity (Metric) 100

Customs Number 7326908595

Content Unit(BMEcat) pcs.

Weight (Metric) 1.92

