

## Specification Sheet

Part Number: MBT8H



Stainless Steel Tie, 7.9" Long, 450lb Tensile Strength, SS316, Metal, 50/pkg

|                     |   |
|---------------------|---|
| Article Number      | 111-94089   |
| Type                | MBT8H   |
| Color               | Metal (ML)  |
| Features & Benefits | <ul style="list-style-type: none"><li>•316 grade stainless steel offers excellent resistance to salt spray, corrosion, weather and chemical resistance.</li><li>•Self locking, ball bearing mechanism for quick and easy installation, either by hand or by tensioning tool.</li><li>•Fully enclosed head prevents dirt or grit from interfering with locking mechanism.</li><li>•High tensile strength for maximum strength and safety on heavy duty applications.</li></ul> |
| Quantity Per        | bag   |

**Product Description**

HellermannTyton's stainless steel ties are designed with a ball bearing locking mechanism to assure high tensile strength and easy insertion when securing hoses, cables, pipes, and more. Stainless steel ties can be used in virtually any indoor, outdoor, or underground application. Grade 316 material is highly resistant to corrosion and widely used in marine environments where chemicals, salts, acids, and temperature extremes may affect the bundling application. MBT stainless steel ties in 316 stainless steel material are also available with a polyester protective coating. This coating creates a barrier and protectant from chemical reactions of dissimilar metals.

**Short Description**

Stainless Steel Tie, 7.9" Long, 450lb Tensile Strength, SS316, Metal, 50/pkg

**Global Part Name**

MBT8H-SS316-ML

**Minimum Tensile Strength (Imperial)**

450.0

**Minimum Tensile Strength (Metric)**

2000.0

**Length L (Imperial)**

7.9

**Length L (Metric)**

201.0

**Identification Plate Position**

none

**Releasable Closure**

No

**Tie Closure**

ball bearing lock

**Variant**

No Serration

**Width W (Imperial)**

0.31

**Width W (Metric)**

7.9

**Bundle Diameter Min (Imperial)**

0.47

**Bundle Diameter Min (Metric)** 12.0

**Bundle Diameter Max (Imperial)** 2.0

**Bundle Diameter Max (Metric)** 50.0

**Thickness T (Imperial)** 0.01

**Thickness T (Metric)** 0.3

**Material** Stainless Steel (SS316)

**Material Shortcut** SS316

**Flammability** Non-Burning

**Halogen free** Yes

**Operating Temperature (Metric)** -112°F to +1000°F (-80°C to +538°C)

**Reach Complaint(Article 33)** Yes

**ROHS Complaint** Yes

**Certification/Specification WEB** DNV | IEC 62275:2006 ABS | IEC 62275:2006

**Package Quantity(Imperial)** 50

**Package Quantity (Metric)** 50

**Customs Number**

7326908595

**Content Unit(BMEcat)**

pcs.

**Weight (Metric)**

11