

## Specification Sheet

Part Number: T18R9C2



Engineered and manufactured for maximum performance and quality. Made from 100% high-quality plastic to ensure efficient recycling.

Inside serration for a strong grip onto bundles.

Easy application either manually or with a tensioning tool.

Bent tail allows for simpler insertion.

Cable Tie, 4" Long, UL Rated, 18lb Tensile Strength, PA66, Natural, 100/pkg

Article Number 112-01819

Type T18R

Color Natural (NA)

Quantity Per bag

Product Description T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

Short Description Cable Tie, 4" Long, UL Rated, 18lb Tensile Strength, PA66, Natural, 100/pkg

|                                     |                 |
|-------------------------------------|-----------------|
| Global Part Name                    | T18R-PA66-NA    |
| Minimum Tensile Strength (Imperial) | 18.0            |
| Minimum Tensile Strength (Metric)   | 80.0            |
| Length L (Imperial)                 | 3.94            |
| Length L (Metric)                   | 100.0           |
| Identification Plate Position       | none            |
| Releasable Closure                  | No              |
| Tie Closure                         | plastic pawl    |
| Variant                             | Inside Serrated |
| Width W (Imperial)                  | 0.10            |
| Width W (Metric)                    | 2.5             |
| Bundle Diameter Min (Imperial)      | 0.06            |
| Bundle Diameter Min (Metric)        | 1.5             |
| Bundle Diameter Max (Imperial)      | 0.87            |
| Bundle Diameter Max (Metric)        | 22.0            |
| Thickness T (Imperial)              | 0.039           |

|                               |                                  |
|-------------------------------|----------------------------------|
| Thickness T (Metric)          | 1.0                              |
| Height H (Metric)             | 3.7                              |
| Material                      | Polyamide 6.6 (PA66)             |
| Material Shortcut             | PA66                             |
| Flammability                  | UL 94 V-2                        |
| Halogen Free                  | Yes                              |
| Operating Temperature         | -40°F to +185°F (-40°C to +85°C) |
| Reach Compliant (Article 33)  | Yes                              |
| ROHS Compliant                | Yes                              |
| Certification/Specification   | UL 62275                         |
| UL Recognized (US)            | Yes                              |
| UL Listed (US and Canada)     | Yes                              |
| UL Recognized (US and Canada) | Yes                              |
| UL Listed (US)                | Yes                              |

Package Quantity (Imperial) 100

Package Quantity (Metric) 100

Customs Number 3926909988