


Specification Sheet

Part Number: CTT20R9M4



Clamp Tie, 4" Long, 20lb Tensile Strength, PA66, Natural, 1000/pkg

Article Number

112-51904

Type

CTT20R

Color

Natural (NA)

Features & Benefits

•Head design contains clamping rails to provide full circumferential compression around bundles. •Bent tail allows for quick insertion into head.

Quantity Per

bag

Product Description

HellermannTyton clamp tie has triangular shaped tabs extending beneath the head for optimal surface contact and complete circumferential compression to 360 degrees. The bent tail design allows quick and simple installations by hand. The clamps are recommended for soft rubber hose applications including fuel, water, and air vacuum lines.

Short Description

Clamp Tie, 4" Long, 20lb Tensile Strength, PA66, Natural, 1000/pkg

Global Part Name

CTT20R-PA66-NA

Minimum Tensile Strength (Imperial)

20.0

Minimum Tensile Strength (Metric)

90.0

Length L (Imperial)

4.0

Length L (Metric)

101.6

Identification Plate Position

none

Releasable Closure

No

Tie Closure

plastic pawl

Variant

Inside Serrated

Width W (Imperial)

0.1

Width W (Metric)

2.5

Bundle Diameter Min (Imperial)

0.06

Bundle Diameter Min (Metric)

1.6

Bundle Diameter Max (Imperial)

0.51

Bundle Diameter Max (Metric)

13.0

Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Flammability	UL 94 V2
Operating Temperature (Metric)	-40°F to +185°F (-40°C to +85°C)
ROHS Complaint	Yes
Certification/Specification WEB	UL
UL Recognized (US)	Yes
UL Recognized (US and Canada)	Yes
Package Quantity(Imperial)	1000
Package Quantity (Metric)	1000
Customs Number	3926909987
Weight (Metric)	0.0003
Weight (Imperial)	0.00062