

## Specification Sheet

Part Number: CTT60R0HIRM4



Clamp Tie, 8" Long, 60lb Tensile Strength, PA66HIRSUV, Black, 1000/pkg

**Article Number** 112-52109

**Type** CTT60R

**Color** Black (BK)

**Features & Benefits**

- High impact and heat stabilized cable ties contain an impact modifier allowing greater flexibility and greater resistance to vibration.
- Head design contains clamping rails to provide full circumferential compression around bundles.
- Bent tail allows for quick insertion into head.

**Quantity Per** bag

<b>Product Description</b>	The 360 Degree compression ties were designed with underside clamping rails to allow for optimal surface contact and complete circumferential compression around the bundle. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
<b>Short Description</b>	Clamp Tie, 8" Long, 60lb Tensile Strength, PA66HIRSUV, Black, 1000/pkg
<b>Global Part Name</b>	CTT60R-PA66HIRHSUV-BK
<b>Minimum Tensile Strength (Imperial)</b>	60.0
<b>Minimum Tensile Strength (Metric)</b>	267.0
<b>Length L (Imperial)</b>	8.0
<b>Length L (Metric)</b>	203.2
<b>Identification Plate Position</b>	none
<b>Releasable Closure</b>	No
<b>Tie Closure</b>	plastic pawl
<b>Variant</b>	Inside Serrated
<b>Width W (Imperial)</b>	0.19
<b>Width W (Metric)</b>	4.7
<b>Bundle Diameter Min (Imperial)</b>	0.06

<b>Bundle Diameter Min (Metric)</b>	1.5
<b>Bundle Diameter Max (Imperial)</b>	1.77
<b>Bundle Diameter Max (Metric)</b>	45.0
<b>Thickness T (Metric)</b>	1.2
<b>Material</b>	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
<b>Material Shortcut</b>	PA66HIRHSUV
<b>Flammability</b>	UL 94 HB
<b>Operating Temperature (Metric)</b>	-40°F to +221°F (-40°C to +105°C)
<b>ROHS Complaint</b>	Yes
<b>Certification/Specification WEB</b>	UL
<b>UL Recognized (US)</b>	Yes
<b>UL Recognized (US and Canada)</b>	Yes
<b>Use Conditions</b>	For Indoor and Outdoor Use
<b>Package Quantity(Imperial)</b>	1000

<b>Package Quantity (Metric)</b>	1000
<b>Customs Number</b>	3926909988
<b>Weight (Metric)</b>	0.0012
<b>Weight (Imperial)</b>	0.0027