

## Specification Sheet

Part Number: CTT60R0HSUVM4

Heat and UV stabilized cable ties provide excellent resistance to high heat and UV exposures

Head design contains clamping rails to provide full circumferential compression around bundles

Bent tail allows for quick insertion into head



Clamp Tie, 8" Long, 60lb Tensile Strength, PA66HS, Black, 1000/pkg

**Article Number** 112-52115

**Type** CTT60R

**Color** Black (BK)

**Quantity Per** bag

**Product Description** The 360 Degree compression ties are designed with underside clamping rails to allow for optimal surface contact and complete circumferential compression around the bundle. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

**Short Description** Clamp Tie, 8" Long, 60lb Tensile Strength, PA66HS, Black, 1000/pkg

**Global Part Name** CTT60R-PA66HSUV-BK

**Minimum Tensile Strength (Imperial)** 60.0

**Minimum Tensile Strength (Metric)** 267.0

**Length L (Imperial)** 8.0

**Length L (Metric)** 203.2

**Identification Plate Position** none

**Releasable Closure** No

**Tie Closure** plastic pawl

**Variant** Inside Serrated

**Width W (Imperial)** 0.19

**Width W (Metric)** 4.7

**Bundle Diameter Min (Imperial)** 0.06

**Bundle Diameter Min (Metric)** 1.5

**Bundle Diameter Max (Imperial)** 1.77

**Bundle Diameter Max (Metric)** 45.0

**Thickness T (Metric)** 1.2

<b>Material</b>	Polyamide 6.6 heat and UV stabilized (PA66HSUV)
<b>Material Shortcut</b>	PA66HSUV
<b>Flammability</b>	UL 94 HB
<b>Operating Temperature</b>	-40°F to +221°F (-40°C to +105°C)
<b>ROHS Compliant</b>	Yes
<b>UL Recognized (US)</b>	Yes
<b>UL Recognized (US and Canada)</b>	Yes
<b>Package Quantity (Imperial)</b>	1000
<b>Package Quantity (Metric)</b>	1000
<b>Customs Number</b>	3926909988