

## Specification Sheet

Part Number: CTT60R0C2



Head design contains clamping rails to provide full circumferential compression around bundles.

Bent tail allows for quick insertion into head.

Clamp Tie, 8" Long, 60lb Tensile Strength, PA66, Black, 100/pkg

Article Number 112-56019

Type CTT60R

Color Black (BK)

Quantity Per bag

Product Description HellermannTyton clamp tie has triangular shaped tabs extending beneath the head for optimal surface contact and complete circumferential compression to 360 degrees. The bent tail design allows quick and simple installations by hand. The clamps are recommended for soft rubber hose applications including fuel, water, and air vacuum lines.

Short Description Clamp Tie, 8" Long, 60lb Tensile Strength, PA66, Black, 100/pkg

Global Part Name CTT60R-PA66-BK

Minimum Tensile Strength (Imperial) 60.0

Minimum Tensile Strength (Metric) 267.0

Length L (Imperial) 8.0

Length L (Metric) 205

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.19

Width W (Metric) 4.7

Bundle Diameter Min (Imperial) 0.06

Bundle Diameter Min (Metric) 1.5

Bundle Diameter Max (Imperial) 1.77

Bundle Diameter Max (Metric) 45.0

Thickness T (Imperial) 0.05

|                               |  |
|-------------------------------|--|
| Thickness T (Metric)          | 1.2  |
| Material                      | Polyamide 6.6 (PA66)                                   |
| Material Shortcut             | PA66   |
| Flammability                  | UL 94 V-2  |
| Operating Temperature         | -40°F to +185°F (-40°C to +85°C)                       |
| Reach Compliant (Article 33)  | Yes  |
| ROHS Compliant                | Yes  |
| Certification/Specification   | UL   ANSI/UL 62275 UL   ANSI/UL 746B UL   ANSI/UL 1565 |
| UL Recognized (US)            | Yes  |
| UL Recognized (US and Canada) | Yes  |
| Package Quantity (Imperial)   | 100  |
| Package Quantity (Metric)     | 100  |
| Customs Number                | 3926909988   |

