

Specification Sheet

Part Number: T120MR0H4



1-Piece Cable Tie/Screw Mount, 4.3" Long, #1/4 Screw, 4.02" Max Bundle Dia, 120lb, PA66, Black, 500/pkg

Article Number	113-00011
Type	T120MR
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none">•Screw mount style creates low insertion and high extraction force.•Choose from several tensile strengths and lengths to accommodate a range of applications.
Quantity Per	bag
Product Description	One-piece Screw Mount Cable Ties fasten with a screw or bolt to provide secure routing of cable bundles. Multiple configurations are available to cover a range of bundle sizes and tensile strengths.
Short Description	1-Piece Cable Tie/Screw Mount, 4.3" Long, #1/4 Screw, 4.02" Max Bundle Dia, 120lb, PA66, Black, 500/pkg

Global Part Name

T120MR-PA66-BK

Minimum Tensile Strength (Imperial)

120.0

Minimum Tensile Strength (Metric)

535.0

Length L (Imperial)

15.6

Length L (Metric)

395.0

Fixation Method

Fixing hole

Identification Plate Position

none

Releasable Closure

No

Tie Closure

plastic pawl

Variant

Inside Serrated

Width W (Imperial)

0.3

Width W (Metric)

7.6

Bundle Diameter Min (Imperial)

0.2

Bundle Diameter Min (Metric)

5.0

Bundle Diameter Max (Imperial)

4.0

Bundle Diameter Max (Metric)

102.0

Thickness T (Imperial)

0.07

Thickness T (Metric)	1.8
Cable Tie Head Length (Imperial)	1.1
Cable Tie Head Width (Imperial)	0.5
Height H (Imperial)	0.31
Height H (Metric)	7.9
Mounting Hole Diameter D (Imperial)	0.26
Mounting Hole Diameter D (Metric)	6.5 mm
Mounting Hole Diameter D Max (Metric)	6.5
Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Flammability	UL 94 V2
Operating Temperature (Metric)	-40°F to +221°F (-40°C to +105°C)
ROHS Complaint	Yes
UL Recognized (US)	Yes
UL Recognized (US and Canada)	Yes

Package Quantity(Imperial)

500

Package Quantity (Metric)

500

Customs Number

3926909987