

## Specification Sheet

Part Number: 113-00060



Reinforcement ribs between the screw mount and cable tie head provide additional strength for added bundle stability and security. Simple one piece design for quick and easy installation.

Secures with a screw or bolt.

1-Pc Cable Tie/Screw Mount, 8.5" Long, .2" Hole, 1.8" Max Bundle Dia, 50lb, PA66HS, Black, 100/pkg

**Article Number** 113-00060

**Type** T50MRX

**Color** Black (BK)

**Quantity Per** bag

**Product Description** Screw Mount Cable Ties attach to existing holes using a screw or bolt to provide a fastening point to secure and route wire and cable bundles. Reinforced ribs between the screw mount and cable tie head provide additional strength for added bundle stability and security.

**Short Description** 1-Pc Cable Tie/Screw Mount, 8.5" Long, .2" Hole, 1.8" Max Bundle Dia, 50lb, PA66HS, Black, 100/pkg

**Global Part Name** T50MRX-PA66HS-BK

**Minimum Tensile Strength (Imperial)** 50.0

**Minimum Tensile Strength (Metric)** 225.0

**Length L (Imperial)** 8.0

**Length L (Metric)** 203.2

**Fixation Method** Fixing hole

**Identification Plate Position** none

**Releasable Closure** No

**Tie Closure** plastic pawl

**Variant** Inside Serrated

**Width W (Imperial)** 0.2

**Width W (Metric)** 4.7

**Bundle Diameter Min (Imperial)** 0.06

**Bundle Diameter Min (Metric)** 1.5

**Bundle Diameter Max (Imperial)** 1.77

**Bundle Diameter Max (Metric)** 45.0

<b>Height H (Imperial)</b>	.24
<b>Height H (Metric)</b>	6.0
<b>Mounting Hole Diameter D (Imperial)</b>	0.2
<b>Mounting Hole Diameter D (Metric)</b>	5.2 mm
<b>Mounting Hole Diameter D Max (Metric)</b>	5.2

**Material** Polyamide 6.6 heat stabilized (PA66HS)

**Material Shortcut** PA66HS

**Flammability** UL 94 V-2

**Operating Temperature** -40°F to +257°F (-40°C to +125°C)

**ROHS Compliant** Yes

**UL Recognized (US)** Yes

**UL Listed (US and Canada)** Yes

**UL Recognized (US and Canada)** Yes

**UL Listed (US)** Yes

**Package Quantity (Imperial)** 100

**Package Quantity (Metric)** 100

**Customs Number** 3926909988