

## Specification Sheet

Part Number: 113-00071

Offset mount allows wire or cable to be attached beside mounting hole instead of directly above it.

Reusable fastener can be extracted from threaded or nonthreaded holes using a 5/16" hex driver.

Delivers high extraction force for reliable performance, yet it's easy to install.

Heat stabilized material provides excellent resistance to high temperatures.

Product Image

Blind Hole Mount Cable Tie for 6.3 mm Hole, 18 mm Offset, 8" L, 50lb, PA66HIRHSUV, Black, 3000/ctn

**Article Number** 113-00071

**Type** T50ROSBHMBTIE

**Color** Black (BK)

**Quantity Per** box

**Product Description** Blind Hole Mount Offset Cable Ties secure bundles beside the mounting hole instead of directly above it. The unique design includes a heat stabilized cable tie and formula-matched, hex-head fastener that features a low insertion force and aggressively resists pull off. Performs equally well in threaded or non-threaded blind holes. Since cable or wire bundle is beside the fastener, the assembly can be removed using a hex driver from the mounting hole without cutting the cable tie. The fastener can then be reused.

**Short Description** Blind Hole Mount Cable Tie for 6.3 mm Hole, 18 mm Offset, 8" L, 50lb, PA66HIRHSUV, Black, 3000/ctn

**Global Part Name** T50ROSBHMBTIE-PA66HIRHSUV-BK

**Minimum Tensile Strength (Imperial)** 50.0

**Minimum Tensile Strength (Metric)** 225.0

**Length L (Imperial)** 8.61

**Length L (Metric)** 218.71

**Offset Length (Imperial)** 0.71

**Offset Length (Metric)** 18.0

**Fixation Method** Blind Plug

**Identification Plate Position** none

**Releasable Closure** No

**Bundle Diameter Min (Imperial)** 0.08

**Bundle Diameter Min (Metric)** 2.0

**Bundle Diameter Max (Imperial)** 1.97

**Bundle Diameter Max (Metric)** 50.0

**Diameter D (Imperial)** 0.70

**Diameter D (Metric)** 17.85

**Material** Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

**Material Shortcut** PA66HIRHSUV

**Operating Temperature** -40°F to +266°F (-40°C to +130°C)

**Reach Compliant (Article 33)** No

**ROHS Compliant** Yes

**Package Quantity (Imperial)** 3000

**Package Quantity (Metric)** 3000

**Customs Number** 3926909988