

Specification Sheet

Part Number: 113-00071

Offset mount allows wire or cable to be attached beside mounting hole instead of directly above it.

Reusable fastener can be extracted from threaded or nonthreaded holes using a 5/16" hex driver.

Delivers high extraction force for reliable performance, yet it's easy to install.

Heat stabilized material provides excellent resistance to high temperatures.



Blind Hole Mount Cable Tie for 6.3 mm Hole, 18 mm Offset, 8" L, 50lb, PA66HIRHSUV, Black, 3000/ctn

Article Number 113-00071

Type T50ROSBHMBTIE

Color Black (BK)

Quantity Per box

Product Description Blind Hole Mount Offset Cable Ties secure bundles beside the mounting hole instead of directly above it. The unique design includes a heat stabilized cable tie and formula-matched, hex-head fastener that features a low insertion force and aggressively resists pull off. Performs equally well in threaded or non-threaded blind holes. Since cable or wire bundle is beside the fastener, the assembly can be removed using a hex driver from the mounting hole without cutting the cable tie. The fastener can then be reused.

Short Description	Blind Hole Mount Cable Tie for 6.3 mm Hole, 18 mm Offset, 8" L, 50lb, PA66HIRHSUV, Black, 3000/ctn
Global Part Name	T50ROSBHMBTIE-PA66HIRHSUV-BK
Minimum Tensile Strength (Imperial)	50.0
Minimum Tensile Strength (Metric)	225.0
Length L (Imperial)	8.61
Length L (Metric)	218.71
Offset Length (Imperial)	0.71
Offset Length (Metric)	18.0
Fixation Method	Blind Plug
Identification Plate Position	none
Releasable Closure	No
Bundle Diameter Min (Imperial)	0.08
Bundle Diameter Min (Metric)	2.0
Bundle Diameter Max (Imperial)	1.97
Bundle Diameter Max (Metric)	50.0

Diameter D (Imperial)	0.70
Diameter D (Metric)	17.85
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Operating Temperature	-40°F to +266°F (-40°C to +130°C)
Reach Compliant (Article 33)	No
ROHS Compliant	Yes
Package Quantity (Imperial)	3000
Package Quantity (Metric)	3000
Customs Number	3926909988