

## Specification Sheet

Part Number: T120MR0HSH4



1-Piece Cable Tie/Screw Mount, 15.6" Long, #1/4" Screw, 4.02" Max Bundle Dia, 120lb, PA66HS, Black, 500/pkg

|                                |  |
|--------------------------------|--|
| <b>Article Number</b>          | 113-00073  |
| <b>Type</b>                    | T120MR   |
| <b>Color</b>                   | Black (BK)   |
| <b>Features &amp; Benefits</b> | <ul style="list-style-type: none"><li>• Part design applies easily to any #1/4" Screw</li><li>• Stud style provides low insertion and high extraction force.</li></ul> |
| <b>Quantity Per</b>            | bag  |
| <b>Product Description</b>     | Screw Mount Cable Ties are made of all plastic and provide a quick and simple method of mounting.  |

|  |  |
|--|--|
| <b>Short Description</b>                   | 1-Piece Cable Tie/Screw Mount, 15.6" Long, #1/4 Screw, 4.02" Max Bundle Dia, 120lb, PA66HS, Black, 500/pkg |
| <b>Global Part Name</b>                    | T120MR-PA66HS-BK   |
| <b>Minimum Tensile Strength (Imperial)</b> | 120.0  |
| <b>Minimum Tensile Strength (Metric)</b>   | 535.0  |
| <b>Length L (Imperial)</b>                 | 15.6   |
| <b>Length L (Metric)</b>                   | 395.0  |
| <b>Fixation Method</b>                     | Fixing hole  |
| <b>Identification Plate Position</b>       | none   |
| <b>Releasable Closure</b>                  | No   |
| <b>Tie Closure</b>                         | plastic pawl   |
| <b>Variant</b>                             | Inside Serrated  |
| <b>Width W (Imperial)</b>                  | 0.3  |
| <b>Width W (Metric)</b>                    | 7.6  |
| <b>Bundle Diameter Min (Imperial)</b>      | 0.20   |
| <b>Bundle Diameter Min (Metric)</b>        | 5.0  |

|  |  |
|--|--|
| <b>Bundle Diameter Max (Imperial)</b>        | 4.02                                   |
| <b>Bundle Diameter Max (Metric)</b>          | 102.0                                  |
| <b>Thickness T (Imperial)</b>                | 0.07                                   |
| <b>Thickness T (Metric)</b>                  | 1.8                                    |
| <b>Cable Tie Head Length (Imperial)</b>      | 1.1                                    |
| <b>Cable Tie Head Width (Imperial)</b>       | 0.5                                    |
| <b>Height H (Imperial)</b>                   | 0.31                                   |
| <b>Height H (Metric)</b>                     | 7.9                                    |
| <b>Mounting Hole Diameter D (Imperial)</b>   | 0.26                                   |
| <b>Mounting Hole Diameter D (Metric)</b>     | 6.5 mm                                 |
| <b>Mounting Hole Diameter D Max (Metric)</b> | 6.5                                    |
| <br>   |  |
| <b>Material</b>                              | Polyamide 6.6 heat stabilized (PA66HS) |
| <b>Material Shortcut</b>                     | PA66HS                                 |
| <b>Flammability</b>                          | UL 94 V2                               |
| <b>Operating Temperature (Metric)</b>        | -40°F to +257°F (-40°C to +125°C)      |

**ROHS Complaint** Yes

**UL Recognized (US)** Yes

**UL Listed (US and Canada)** Yes

**UL Recognized (US and Canada)** Yes

**UL Listed (US)** Yes

**Package Quantity(Imperial)** 500

**Package Quantity (Metric)** 500

**Customs Number** 3926909988