

## Specification Sheet

Part Number: T120MR0HSH4



Part design applies easily to any #1/4" screw  
Stud style provides low insertion and high extraction force

1-Piece Cable Tie/Screw Mount, 15.6" Long, #1/4 Screw, 4.02" Max Bundle Dia, 120lb, PA66HS, Black, 500/pkg

<b>Article Number</b>	113-00073
<b>Type</b>	T120MR
<b>Color</b>	Black (BK)
<b>Quantity Per</b>	bag
<b>Product Description</b>	Screw Mount Cable Ties are made of all plastic and provide a quick and simple method of mounting.
<b>Short Description</b>	1-Piece Cable Tie/Screw Mount, 15.6" Long, #1/4 Screw, 4.02" Max Bundle Dia, 120lb, PA66HS, Black, 500/pkg
<b>Global Part Name</b>	T120MR-PA66HS-BK

<b>Minimum Tensile Strength (Imperial)</b>	120.0
<b>Minimum Tensile Strength (Metric)</b>	535.0
<b>Length L (Imperial)</b>	15.6
<b>Length L (Metric)</b>	395.0
<b>Fixation Method</b>	Fixing hole
<b>Identification Plate Position</b>	none
<b>Releasable Closure</b>	No
<b>Tie Closure</b>	plastic pawl
<b>Variant</b>	Inside Serrated
<b>Width W (Imperial)</b>	0.3
<b>Width W (Metric)</b>	7.6
<b>Bundle Diameter Min (Imperial)</b>	0.20
<b>Bundle Diameter Min (Metric)</b>	5.0
<b>Bundle Diameter Max (Imperial)</b>	4.02
<b>Bundle Diameter Max (Metric)</b>	102.0
<b>Thickness T (Imperial)</b>	0.07
<b>Thickness T (Metric)</b>	1.8

<b>Cable Tie Head Length (Imperial)</b>	1.1
<b>Cable Tie Head Width (Imperial)</b>	0.5
<b>Height H (Imperial)</b>	0.31
<b>Height H (Metric)</b>	7.9
<b>Mounting Hole Diameter D (Imperial)</b>	0.26
<b>Mounting Hole Diameter D (Metric)</b>	6.5 mm
<b>Mounting Hole Diameter D Max (Metric)</b>	6.5

**Material** Polyamide 6.6 heat stabilized (PA66HS)

**Material Shortcut** PA66HS

**Flammability** UL 94 V-2

**Operating Temperature** -40°F to +257°F (-40°C to +125°C)

**ROHS Compliant** Yes

**UL Recognized (US)** Yes

**UL Listed (US and Canada)** Yes

**UL Recognized (US and Canada)** Yes

<b>UL Listed (US)</b>	Yes
<b>Package Quantity (Imperial)</b>	500
<b>Package Quantity (Metric)</b>	500
<b>Customs Number</b>	3926909988